

BX & B01 SERIES



RESIDENTIAL SOLUTIONS

From acres of estate to clear or simply needing to get the car out of the garage after a storm, Kubota has snow removal solutions that are up to the task. Kubota offers a wide variety of versatile attachments built as tough as any Canadian winter. The result is a total solution that gets the snow out of your way.



SNOWBLOWER



SWEEPER



SNOW BLADE



SNOW PUSHER

ATTACHMENT SPECS

		Description	BX2812	BX2826	STB0554	STB0560	STB1060	STB01072
SNOW BLADE	Hitch	Hitch Type	Front, K-Connect	Front, K-Connect	Loader Mount	Loader Mount	Loader Mount	Loader Mount
	General	Blade Type	Straight Blade	V Blade	Straight Blade	Straight Blade	Straight Blade	Straight Blade
		Angle Type	Hydraulic	Hydraulic	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)
		Maximum Width (Length)	60″	60″	54″	60″	60″	72″
		Maximum Pivot Angle (Degrees)	30 degrees	30 degrees	24 degrees	24 degrees	30 degrees	30 degrees
		Cutting Width @ Max Degrees Angle	52″	In V Position 54″ In Scoop Position 52″	49″	55″	52″	62″
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable
		Skid Shoes	STD & Adjustable	STD & Adjustable	STD & Adjustable	STD & Adjustable	STD & Adjustable	STD & Adjustable
		Moldboard Height	19 3/4″	16 5/8″ center 20″ both end	17″	17″	22″	22″
		Moldboard Thickness	7 GA	14 GA	12 GA	12 GA	12 GA	12 GA
		Base Equipment Weight	230 lbs	280 lbs	278 lbs	288 lbs	368 lbs	390 lbs
	Optional Equipment	Poly Cutting Edge	Yes	–	Yes	Yes	Yes	Yes

ATTACHMENT SPECS

		Description	BX2816	BX2830	BX2822A	K51-20-06	K54-22-06
SNOWBLOWER	General	Hitch Type (Front /Rear Mount)	Front, K-Connect	Front, K-Connect	Front, K-Connect	Rear, 3 Pt	Rear, 3 Pt
		Blower Type	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage
		Approx. Shipping Weight	287 lbs	500 lbs	520 lbs	555 lbs	575 lbs
		Overall Width	50″	49 1/4″	56 1/4″	51 1/2″	54 1/2″
		Working Width	49 3/4″	48″	55″	50 1/2″	53 1/2″
		Working Height	20″	20″	20″	24 1/2″	25 1/2″
		Overall Length (w/hitch)	26 3/8″	30″	30″	36 1/2″	36 1/2″
	Impeller	Impeller Diameter	15 3/4″	15 3/4″	15 3/4″	20″	22″
		Number of Impeller Blades	4	4	4	4	4
	Auger	Auger Drive	Chain #40	Worm Gear	Worm Gear	Chain #50	Chain #60
		Auger Diameter	12 3/4″	12 3/4″	12 3/4″	15″	15″
	Housing	Housing Thickness	14 GA	12 GA	12 GA	12 GA	12 GA
		Side Panel Thickness	11 GA	7 GA	7 GA	11 GA	11 GA
	Chute	Rotation of Chute	Manual (Hydraulic Opt)	Hydraulic with motor	Hydraulic with motor	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)
		Deflector Adjustment	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)
	Cutting Edge	Replaceable	Yes	Yes	Yes	Yes	Yes
	Skid Shoes	Replaceable and Adjustable	Yes	Yes	Yes	Yes	Yes

		Description	BX2814
SWEEPER	Hitch	Hitch Type	Front, K-Connect
	General	Height	25″
		Overall Width	62″
		Working Width	56″
		Maximum Pivot Angle (Degrees)	25 degrees
		Working Width @ Max Angle	48 1/2″
		Brush Type	100% polypropylene
		Brush Speed Range	270 RPM @ 3000 RPM
		Main Housing Thickness	16 GA
		Side Housing Thickness	12 GA
		Approx. Shipping Weight (LBS.)	480 lbs
	Optional Equipment	Dust Deflector	Optional

		Description	SPL0548	SPL0560
LOADER MOUNT SNOW PUSHER	Hitch	Hitch Type	Loader Mount	Loader Mount
	General	Working Width	48″	60″
		Approx. Capacity	9 ft^3	12 ft^3
		Weight (Poly Optional)	168 lbs	190lbs
		HP Range	Max 28 HP	Max 28 HP
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable
		Moldboard Thickness	12 GA	12 GA
		Side Panel Thickness	7 GA	7 GA



AVAILABLE BX SERIES MODELS:

BX1880
BX2190
BX2390
BX2690
BX2390S
BX2690S
BX2380
BX2680
BX23S

AVAILABLE B01 SERIES MODELS:

B2301
B2601
B2401

