



Digita

Footswitch, manual, or PLC controlled operation

· Ideally suited for Dymax or other pneu-

matically actuated dispense valves

- · Easy to operate and maintain
- Manual or timed dispense modes
- 0,001 to 9,999 second range, settable in 0,001 second increments
- Universal power supply and power plug adapters
- Compact and lightweight

DVC-345 Digital Valve Controller

The DVC-345 digital valve controller provides precise and consistent valve actuation without complex programming. Its internal 4-way solenoid valve operates Dymax or other pneumatic dispense valves. This controller may be operated via footswitch, manual front panel switch, or remote PLC. Cycle time may be set in a range from 0,001 to 9,999 seconds in 0,001 second increments. Front panel mounted controls provide a valve prime function, cycle adjustment, manual or timed dispense, and a multi-color LCD timer display. The controller also includes a DC wall-mount adapter with five global power adapters to convert the unit to 24 VDC, ensuring precise and repeatable shots.

Specifications	
Part Number	T11146
Power Requirements	120VAC, 240VAC, 50/60 Hz, 1/10 Amp
Air Pressure Requirements	60 psi minimum/100 psi maximum, 25 micron filtered air
Operation	Manual, footswitch, or PLC
Timer	Programmable to 0.001 to 9.999 seconds in 0.001 second increments
Cycle Time	>15 milliseconds
Dimensions (W x D x H)	15,9 cm x 20,3 cm x 8,9 cm [6,25" x 8,0" x 3,5"]
Weight	1,27 kg [2,8 lbs]
Unit Warranty	1 year from purchase



Figure 1. Controller Dimensions





Americas

USA | +1.860.482.1010 | info@dymax.com

Europe

Germany | +49 611.962.7900 | info_de@dymax.com |reland | +353 21.237.3016 | info_ie@dymax.com

Asia

 $\label{eq:comparison} Singapore \mid +65.67522887 \mid info_ap@dymax.com \\ China \mid +86.755.83485759 \mid dymaxasia@dymax.com \\ Hong Kong \mid +852.2460.7038 \mid dymaxasia@dymax.com \\ Korea \mid +82.31.608.3434 \mid info_kr@dymax.com \\ \end{cases}$

©2020 Dymax Corporation. All rights reserved. All trademarks in this guide, except where noted, are the property of, or used under license by, Dymax Corporation, U.S.A.

The data contained in this bulletin is of a general nature and is based on laboratory test conditions. Dymax Europe GmbH does not warrant the fitness of the product for the intended application. Any warranty applicable to products, its application and use is strictly limited to that contained in Dymax Europe GmbHs General Terms and Conditions of Sale published on our website. Dymax Europe GmbH does not assume any responsibility for test or performance results obtained by users. It is the user's responsibility to the termine the suitability for the product application and purposes and the suitability for use in the user's intended manufacturing apparatus and methods. The user should adopt such precautions and use guidelines as may be reasonably advisable or necessary for the protection of property and persons. Nothing in this bulletin shall act as a representation that the product use or application will not infringe a patent owned by someone other than Dymax Corporation or act as a grant of license under any Dymax Corporation Patent. Dymax Europe GmbH recommends that each user adequately test its proposed use and application of the products before actual repetitive use, using the data contained in this bulletin as a general guide.

PB003EU 8/75/2012**