



Digital Valve Controller

DVC-345

- Ideally suited for Dymax or other pneumatically actuated dispense valves
- Footswitch, manual, or PLC controlled operation
- · Easy to operate and maintain
- Manual or timed dispense modes
- 0.001 to 9.999 second range, settable in 0.001 second increments
- Universal power supply and power plug adapters
- Compact and lightweight

The DVC-345 digital valve controller provides precise and consistent valve actuation without complex programming. Its internal 4-way solenoid valve operates Dymax or other pneumatic dispense valves. This controller may be operated via footswitch, manual front panel switch, or remote PLC. Cycle time may be set in a range from .001 to 9.999 seconds in .001 second increments. Front panel mounted controls provide a valve prime function, cycle adjustment, manual or timed dispense, and a multi-color LCD timer display. The controller also includes a DC wall-mount adapter with five global power adapters to convert the unit to 24 VDC, ensuring precise and repeatable shots.

| Specifications | |
|---------------------------|---|
| Part Number | T11146 |
| Power Requirements | 120VAC, 240VAC, 50/60 Hz, 1/10 amp |
| Air Pressure Requirements | 60 psi minimum/100 psi maximum, 25 micron filtered air |
| Operation | Manual, footswitch, or PLC |
| Timer | Programmable to 0.001 to 9.999 seconds in 0.001 second increments |
| Cycle Time | >15 milliseconds |
| Dimensions (W x D x H) | 6.25" x 8" x 3.5" (15.9 cm x 20.3 cm x 8.9 cm) |
| Weight | 2.8 lbs (1.27 kg) |
| Unit Warranty | 1 year from purchase |



Figure 1. Controller Dimensions





www.dymax.com

Americas

USA | +1.860.482.1010 | info@dymax.com

Europe

Germany | +49 611.962.7900 | info_de@dymax.com Ireland | +353 21.237.3016 | info_ie@dymax.com

Acia

Singapore | +65.67522887 | info_ap@dymax.com China | +86.755.83485759 | dymaxasia@dymax.com Hong Kong | +852.2460.7038 | dymaxasia@dymax.com Korea | +82.31.608.3434 | info_kr@dymax.com