



FLOORSPACE Contract

L	JXUR	YV	INYL	FLO	ORIN	G

$\int 1 +$	\int	1	to
Product	Perform	ance 1.	esting
~ 1			

ASTM F2055 Size and Tolerance	Passes	As specified 0.016 in./lin.ft
ASTM F386 Thickness	Passes	As specified 0.005 in./lin.ft
ASTM F2055 Squareness	Passes	Max. 0.010 in.
ASTM F1914 Residual Indentation	Passes	Avg. < 8%
ASTM F137 Flexibility	Passes	1 in (25.4mm) mandrel / no crack or break
ASTM F2199 Dimension Stability	Passes	< 0.020in./ft
ASTM F925 Chemical Resistance	Passes	No change/Slight change
ASTM F1514 Resistance to Heat	Passes	< 8 (delta E) avg.
ASTM F1515 Resistance to Light	Passes	< 8 (delta E) avg.
ASTM E648 Critical Radiant Flux	Class 1	Class 1 (< 0.45 W/cm²)
ASTM E662 Optical Smoke Density	Passes	< 450
ASTM C1028 Slip Resistance	Passes	ADA Compliant(> 0.50)
ASTM F970 Static Load	1000 psi	250 psi(< 0.005")



2.0mm **Edge Detail:** Square 100% Virgin Vinyl **Enhanced UV Urethane Coating** 51.24 2562

Material:

Finish:

SF/Ctn:

SF/Pallet:

Recommended Adhesive(s): **Polish Required:** Product Warranty - 6mil:

Product Warranty - 12mil:

Tom Duffy approved LVT adhesive None 15 years Residential **5 years Light Commercial** 20 years Residential 10 years Light Commercial

FOR MORE INFORMATION OR TO BUY, PLEASE CONTACT YOUR TOM DUFFY SALES REP, YOUR LOCAL TOM DUFFY BRANCH OR VISIT US AT