

# STANTON

## DECORATIVE | LAMINATE

### NuvoMax 8 Series – Decorative Laminate Specifications

#### Specifications

Styles	Beach House, Haywood, Peak Point, Provincial, Sherwood
Size	7.7" W x 48" L
Construction	High Density Fiber Board
Wear Layer	0.1mm Melamine
Total Thickness	12mm (includes 2mm IXPE Pad)
Locking System	Välinge 2G
Edge Treatment	Pressed bevel on 4 sides
Rating	AC4
Packaging (per carton)	6 pcs / 15.30 ft. <sup>2</sup> / 28.55 lbs.
Installation Method	Floating Tight Lock
Expansion and Transitions Required	1/2" expansion and relief against all vertical obstructions. Transitions are required for all installations exceeding 65' in length or 65' in width (4,200 ft. <sup>2</sup> ), any doorway or cased opening under 32 inches in width.
Waterproofing Wet Areas	1/2" expansion space/use 1/2" foam backer rod and 100% silicone filled in all expansion gaps and transitions. With this product no floor drains are allowed.
Radiant Floor	Installation approved over embedded systems only

#### Material Classification: Class 3: Medium Commercial

Testing: NALFA LF-01-2001	Results	Testing: NALFA LF-01-2001	Results
3.1 Static Load	Class 4	Acoustic STC (ASTM E413-16)	STC=68
3.2 Thickness Swell	Class 3	Acoustic IIC (ASTM E989-6)	IIC=68
3.3 Light Resistance	Class 4	Reducing Impact Sound	Δ22
3.4 Cleanability/Stain	Class 4	Fire Resistance CHF (ASTM E 648/NFPA 253)	Compliant
3.5 Large Ball Impact	Class 4	Smoke Density ASTM E662/NAPA 258	Compliant
3.6 Small Ball Impact	Class 4	T-Seam Tightness	Compliant
3.7 Wear	Class 3		
3.8 Wear	Class 4		
3.9 Castor Chair	Class 4		
3.10 Surface Bonding	Class 3		
3.11 Formaldehyde	Class 4		
3.12 Width and Length Accuracy	Class 4		
3.13 Openings	Class 4		
3.14 Ledging	Class 4		

#### Environmental Data

Indoor Air Quality  
LEED Scoreboard

#### Description

This product is GREENGUARD Gold certified.  
Available on request



#### Warranty

Lifetime Surface Waterproof  
Limited Lifetime Residential  
15-Year Medium Commercial