STANTON

DECORATIVE | LAMINATE

NuvoMax 8 Series - Decorative Laminate Specifications

Specifications Description

Styles Beach House, Haywood, Peak Point, Provincial, Sherwood

Size 7.7" W x 48" L Specifications Description

Construction High Density Fiber Board

Wear Layer 0.1mm Melamine

Total Thickness 12mm (includes 2mm IXPE Pad)

Locking System Välinge 2G

Edge Treatment Pressed bevel on 4 sides

Rating AC4

Packaging (per carton) 6 pcs / 15.30 ft.² / 28.55 lbs.

Installation Method Floating Tight Lock

Expansion and Transistions Required 1/2" expansion and relief against all vertical obstructions. Transistions are required for all

installations exceeding 50' in length or 50' in width (2,500 ft.2), any doorway or cased opening

under 32 inches in width.

Waterproofing Wet Areas 1/2" expansion space/use 1/2" foam backer rod and 100% silicone filled in all expansion gaps

and transitions. With this product no floor drains are allowed.

Material Classification: Class 3: Medium Commercial

Testing: NALFA LF-01-2001		Results
3.1	Static Load	Class 4
3.2	Thickness Swell	Class 3
3.3	Light Resistance	Class 4
3.4	Cleanability/Stain	Class 4
3.5	Large Ball impact	Class 4
3.6	Small Ball Impact	Class 4
3.7	Wear	Class 3
3.8	Wear	Class 4
3.9	Castor Chair	Class 4
3.10	Surface Bonding	Class 3
3.11	Formaldehyde	Class 4
3.12	Width and Length Accuracy	Class 4
3.13	Openings	Class 4
3.14	Ledging	Class 4

Testing: NALFA LF-01-2001	Results
Acoustic STC (ASTM E413-16)	STC=68
Acoustic IIC (ASTM E989-6)	IIC=68
Reducing Impact Sound	Δ22
Fire Resistance CHF (ASTME 648/NFPA 253)	Compliant
Smoke Density ASTM E662/NAPA 258	Compliant
T-Seam Tightness	Compliant

Environmental Data Description

Indoor Air Quality This product is GreenGuard Gold certified.

LEED Scoreboard Available on request

Warranty Lifetime Surface Waterproof

Limited Lifetime Residential 15-Year Medium Commercial

