

STANTON

DECORATIVE | LAMINATE

NuvoLux 8 Series – Decorative Laminate Specifications

Specifications

Style	Hickory Lake
Size	7.7" W x 48" L
Construction	High Density Fiber Board
Wear Layer	0.1mm Melamine
Total Thickness	12mm (includes 2mm IXPE Pad)
Locking System	i4F Drop Lock
Edge Treatment	Pressed bevel on 4 sides
Rating	AC5
Packaging (per carton)	6 pcs / 15.11 ft. ² / 29.02 lbs.
Installation Method	Floating Tight Lock
Expansion and Transitions Required	1/2" expansion and relief against all vertical obstructions. Transitions are required for all installations exceeding 50' in length or 50' in width (2,500 ft. ²), any doorway or cased opening under 32 inches in width.
Waterproofing Wet Areas	1/2" expansion space/use 1/2" foam backer rod and 100% silicone filled in all expansion gaps and transitions. With this product no floor drains are allowed.
Radiant Floor	Installation approved over embedded systems only

Material Classification: Class 3: Medium Commercial

Testing: NALFA LF-01-2001		Results	Testing: NALFA LF-01-2001		Results
3.1	Static Load	Class 4	Acoustic STC (ASTM E413-16)		STC=68
3.2	Thickness Swell	Class 3	Acoustic STC (ASTM E989-6)		STC=68
3.3	Light Resistance	Class 4	Reducing Impact Sound		Δ22
3.4	Cleanability/Stain	Class 4	Fire Resistance CHF (ASTME 648/NFPA 253)		Compliant
3.5	Large Ball Impact	Class 4	Smoke Density ASTM E662/NAPA 258		Compliant
3.6	Small Ball Impact	Class 4	T-Seam Tightness		Compliant
3.7	Wear	Class 4			
3.8	Wear	Class 4			
3.9	Castor Chair	Class 4			
3.10	Surface Bonding	Class 4			
3.11	Formaldehyde	Class 4			
3.12	Width and Length Accuracy	Class 4			
3.13	Openings	Class 4			
3.14	Ledging	Class 4			

Environmental Data

Indoor Air Quality
LEED Scoreboard

Description

This product is GreenGuard Gold and FloorScore certified.
Available on request

Warranty

Lifetime Surface Waterproof
Limited Lifetime Residential
20-Year Medium Commercial



STANTON

DECORATIVE | LAMINATE

NuvoLux 8 Series – Decorative Laminate Specifications

Specifications

Styles	Adirondacks, Brentwood, Studio Grove
Size	7.7" W x 60" L
Construction	High Density Fiber Board
Wear Layer	0.1mm Melamine
Total Thickness	12mm (includes 2mm IXPE Pad)
Locking System	i4F Drop Lock
Edge Treatment	Pressed bevel on 4 sides
Rating	AC5
Packaging (per carton)	6 pcs / 18.99 ft. ² / 36.47 lbs.
Installation Method	Floating Tight Lock
Expansion and Transitions Required	1/2" expansion and relief against all vertical obstructions. Transitions are required for all installations exceeding 50' in length or 50' in width (2,500 ft. ²), any doorway or cased opening under 32 inches in width.
Waterproofing Wet Areas	1/2" expansion space/use 1/2" foam backer rod and 100% silicone filled in all expansion gaps and transitions. With this product no floor drains are allowed.
Radiant Floor	Installation approved over embedded systems only

Material Classification: Class 3: Medium Commercial

Testing: NALFA LF-01-2001		Results	Testing: NALFA LF-01-2001		Results
3.1	Static Load	Class 4	Acoustic STC (ASTM E413-16)		STC=68
3.2	Thickness Swell	Class 3	Acoustic STC (ASTM E989-6)		STC=68
3.3	Light Resistance	Class 4	Reducing Impact Sound		Δ22
3.4	Cleanability/Stain	Class 4	Fire Resistance CHF (ASTME 648/NFPA 253)		Compliant
3.5	Large Ball Impact	Class 4	Smoke Density ASTM E662/NAPA 258		Compliant
3.6	Small Ball Impact	Class 4	T-Seam Tightness		Compliant
3.7	Wear	Class 4			
3.8	Wear	Class 4			
3.9	Castor Chair	Class 4			
3.10	Surface Bonding	Class 4			
3.11	Formaldehyde	Class 4			
3.12	Width and Length Accuracy	Class 4			
3.13	Openings	Class 4			
3.14	Ledging	Class 4			

Environmental Data

Indoor Air Quality
LEED Scoreboard

Description

This product is GreenGuard Gold and FloorScore certified.
Available on request

Warranty

Lifetime Surface Waterproof
Limited Lifetime Residential
20-Year Medium Commercial

