

STANTON

FINE HARDWOOD

SoHo

6" French White Oak (Coordinating pattern plank: SoHo Peak)

SPECIES	TOP LAYER	French White Oak
	CORE	Spruce
	BACK	Pine or Spruce Balancing Layer
	GRADE	Country Grade
SIZES	PLANK DIMENSION	6" x 71" (RL 24"-71")
	THICKNESS	9/16"
	TOP LAYER	3mm Live Sawn
	CORE	9.5mm (13/32")
	BACK	1.5mm (1/16")
	EDGE	Micro Bevel, 4 Sides
CONSTRUCTION	ENGINEERED WOOD	
	FINISH	UV-cured Polyurethane, nano carbide-enhanced anti-scratch top coat, ultra-matte, 6-8 % gloss, Solvent free, 100% solid, Non-off gassing, ECO-certified
	GLUE	Phenolic Resin glue, EPA TSCH title 6 compliant
APPLICATION	Floor and Wall	
INSTALLATION	Staple, Glue or Floating installation. Radiant Heat-compatible over wood or concrete subfloor	
PACKING	23.3 SF/carton – 48 cartons/pallet – 1,116.0 SF/pallet	
WARRANTY	25-Year Residential Surface Finish	
	3-Year Light Commercial Surface Finish	
	Lifetime Structural Warranty	

TESTS	EMISSIONS TEST	CA-DPH spec 01350, Prop65: Pass
	CRITICAL RADIANT FLUX	0.51 w/cm ² ASTM E 648-06. >Class 1 NFPA Life Safety Code 101, IBC 804.2
	SURFACE BURNING	F 110 – S 400 ASTM E84
	SMOKE DENSITY	Average Dmc 463 Flaming – 512 Non Flaming ASTM E 662-05
	COEFFICIENT OF FRICTION	.96 Dry Standard Neolite ASTM D 2394
	SLIP RESISTANCE	W .86 D .85 ASTM C1028
	MOISTURE CONTENT	>6% to <9% ASTM D 4442
	DELAMINATION TEST	ANSI/HPVA Bond Line Test 100% pass

GREEN BUILD STATEMENT

SoHo may also contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems EQc4, as it uses adhesives that meet the SCAQMD rule #1168. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

CERTIFIED MANUFACTURING

- GREENGUARD Gold, California Prop 65 Certified
- Lacey Act Compliance
- Adhesive used in manufacturing, meet and exceed E0 standard.
- No halogenated hydrocarbons, herbicides, heavy metals



Elevated by design.

stantondesign.com