

# STANTON

100% WATERPROOF WPC

## Natural Beauty Lux 7 Series Specification

**STYLES: Webster, Regal Manor, Colebrook**

### Specifications

Specifications	Description
Construction	Solid WPC Core
Total Thickness	10mm (0.55mm Wear Layer / 2mm Topper / 6mm Waterproof WPC Core / 2mm IXPE Pad)
Wear Layer Thickness	22 mils (0.50mm)
Locking System	Unilin Uniclic
Edge Treatment	Pressed Bevel on 4 sides
Faces/Embossing	5 / EIR / 4-6%
Size	7" Wide x 60" Long
Packaging	Per Carton: 8 pcs / 23.43 ft. <sup>2</sup> / 32.19 lbs. / 55 boxes per pallet / 1,288.61 ft. <sup>2</sup> per pallet
Installation Method	Floating / Glue Down
Expansion and Transitions Required	¼" expansion and relief against all vertical obstructions. Installation exceeding ½" expansion and relief against all vertical obstructions.
Waterproofing Wet Areas	½" expansion space/use ½" foam backer rod and 100% silicone filled in all expansion gaps, and transitions. With this product no floor drains are allowed
Radiant Floor	Installation Approved Over Embedded Systems Only

### Material Classification:

Test Methods	Results
ASTM F2199 Dimensional Stability W/L	≤0.2%
ASTM F2199 Dimensional Stability Curling/Bowing	≤2mm
ASTM F2055 Squareness	≤0.25mm
ASTM F1914 Residual Indentation	≤0.18mm
ASTM F970-17 Static Load	≤0.13mm
ASTM E648 Flooring Radiant Panel	Class 1
ASTM D2047 Slip Resistance	> 0.5
ASTM E492 Acoustic IIC	60
ASTM E90 Acoustic STC	65
ASTM F1515 Resistance to Light	ΔE* < 8
ASTM F925 Chemical Resistance	Rating 0
ASTM F1514 Resistance to Heat	ΔE* < 8

### Environmental Data

Indoor Air Quality  
LEED Scoreboard

### Description

This product is Assure Certified  
Available on request



### Warranty

Lifetime Surface Waterproof  
Limited Lifetime Residential  
10-Year Medium Commercial