## S T A N T O N

## Seaport 9.5" Baltic Ash

SPECIES	TOP LAYER CORE BACK GRADE	Baltic Ash Spruce Pine or Spruce Balancing Layer Country Grade
SIZES	PLANK DIMENSION THICKNESS TOP LAYER CORE BACK EDGE	9 ½" x 82 5/8" (RL 24" - 82 5/8") 5/8" 4mm Live Sawn 9.5mm (13/32") 1.5mm (1/16") Micro Bevel, 4 Sides
CONSTRUCTION	ENGINEERED WOOD FINISH GLUE	UV-cured Polyurethane, nano carbide-enhanced anti-scratch top coat, ultra-matte, 6-8 % gloss, Solvent free, 100% solid, Non-off gassing, ECO-certified EPI adhesive, Free of formaldehyde, EPA compliant
APPLICATION	Floor and Wall	
INSTALLATION	Staple, Glue or Flo	ating installation. Radiant Heat-compatible over wood or concrete subfloor
PACKING	32.55 SF/carton - 4	44 cartons/pallet – 1,432.20 SF/pallet
WARRANTY	50-Year Residenti 5-Year Light Comr Lifetime Structura	nercial Surface Finish
TESTS	EMISSIONS TEST	CA-DPH spec 01350, Prop65: Pass
CRITICAL RADIANT FLUX		0.51 w/cm² ASTM E 648-06. >Class 1 NFPA Life Safety Code 101, IBC 804.2
SURFACE BURNING		F 110 – S 400 ASTM E84
SMOKE DENSITY		Average Dmc 463 Flaming – 512 Non Flaming ASTM E 662-05
	SIVIORE DEINSIT	
COEFFIC	CIENT OF FRICTION	.96 Dry Standard Neolite ASTM D 2394
COEFFIC		
	CIENT OF FRICTION	.96 Dry Standard Neolite ASTM D 2394

## **GREEN BUILD STATEMENT**

Seaport may also contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems EQc4, as it uses adhesives that meet the SCAQMD rule #1168 and it contains no added urea formaldehyde, as required by LEED®. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

## **CERTIFIED MANUFACTURING**

- GREENGUARD Gold, California Prop 65 Certified
- Lacey Act Compliance
- Adhesive used in manufacturing, meet and exceed E0 standard
- No added urea formaldehyde, no halogenated hydrocarbons, herbicides, heavy metals



MEMBER

nw

stantondesign.com