

STANTON

100% WATERPROOF WPC

Natural Beauty Basics Specification

STYLES: Old World, Alpine, Arcadia

Specifications

Specifications	Description
Construction	Solid WPC Core
Total Thickness	6.5 mm (0.50 mm Wear Layer / 1.5mm Topper / 4mm Waterproof WPC Core / 1mm IXPE Pad)
Wear Layer Thickness	20 mils (0.50mm)
Locking System	Unilin Uniclic
Edge Treatment	Micro Bevel on 4 sides
Faces/Embossing/Gloss	5 / All-Over Emboss / 5-8%
Size	7" Wide x 60" Long
Packaging	Per Carton: 8 pcs / 23.72 ft. ² / 32.02 lbs. / 60 boxes per pallet / 1,422.90 ft. ² per pallet
Installation Method	Floating / Glue Down
Expansion and Transitions Required	½" expansion and relief against all vertical obstructions.
Waterproofing Wet Areas	½" expansion space/use ½" foam backer rod and 100% silicone filled in all expansion gaps, and transitions. With this product no floor drains are allowed
Radiant Floor	Installation Approved Over Embedded Systems Only

Material Classification:

Test Methods	Results
ASTM F2199 Dimensional Stability W/L	W0.04%-0.05%/L0.12%-0.16%
ASTM F2199 Dimensional Stability Curling/Bowing	≤1mm
ASTM F2055 Squareness	≤0.25mm
ASTM F1914 Residual Indentation	0.06mm
ASTM F970-17 Static Load	0.12mm
ASTM E648 Flooring Radiant Panel	≤450
ASTM D2047 Slip Resistance	Dry 0.75
ASTM E492 Acoustic IIC	62dB
ASTM E90 Acoustic STC	62dB
ASTM F1515 Resistance to Light	ΔE≤2
ASTM F925 Chemical Resistance	Rating 0
ASTM F1514 Resistance to Heat	ΔE≤0.5

Environmental Data

Indoor Air Quality
LEED Scoreboard

Description

This product is Assure Certified
Available on request



Warranty

Limited Lifetime Residential Surface Waterproof
Limited Lifetime Residential
10-Year Medium Commercial