

# STANTON

DECORATIVE | WATERPROOF SPC

## Floors 2000 Collection Specification STYLE: Rejuvenation

### Specifications

Construction	Solid SPC Core
Total Thickness	6mm (0.50mm Wear Layer / 4.5mm SPC Core / 1.5mm IXPE Pad)
Wear Layer Thickness	20 mils (0.50mm)
Locking System	Välinge 2G
Edge Treatment	Painted Bevel on 4 sides
Embossing	Stone Texture
Pattern Repeat	6 Planks
Rating	Assure Certified
Size	12" Wide x 24" Long
Packaging	Per Carton: 14 pcs / 20.03 ft. <sup>2</sup> / 36.60 lbs. / 66 boxes per pallet / 1,321.73 ft. <sup>2</sup> per pallet
Installation Method	Floating / Glue Down
Expansion and Transitions Required	½" expansion and relief against all vertical obstructions.
Waterproofing Wet Areas	½" expansion space/use ½" foam backer rod and 100% silicone filled in all expansion gaps, and transitions. With this product no floor drains are allowed
Radiant Floor	Installation Approved Over Embedded Systems Only

### Material Classification:

Test Methods	Results
ASTM F2199 Dimensional Stability W/L	Passes - Max 0.020 inches
ASTM F2199 Dimensional Stability Curling/Bowing	Passes - Max 0.020 inches
ASTM F2055 Squareness	Passes - Max 0.010 inches
ASTM F1914 Residual Indentation	0.001 Inch
AATCC 134 Electrostatic Propensity Leather	Step Average 0.8 kv Scuff Average 1.3 kv
AATCC 134 Electrostatic Propensity Neo-lite	Step Average 2.2 kv Scuff Average 3.3kv
ASTM F970-17 Static Load	0.002 inches
ASTM E648 Flooring Radiant Panel	Meets or Exceeds Class 1 - 0.84 Watts/Square CM
ASTM E662 Smoke Density Flaming	Passes - Do Not Exceed 450 DMC
ASTM E662 Smoke Density Non Flaming	Passes - Do Not Exceed 450 DMC
ANSI A137.1 Dynamic Coefficient of Friction	0.037
ASTM D2047 Slip Resistance	
ASTM E492 Acoustic IIC	65
ASTM E492 Acoustic IIC Δ	20
ASTM E90 Acoustic STC	62
ASTM F1515 Resistance to Light	Passes ≤ 8.0 Δ
ASTM F925 Chemical Resistance	Passes - 0.00% Change
ASTM F1514 Resistance to Heat	Δ≤0.45 Gray Scale Rating 4.5
ASTM EN 16094 Micro-Scratch Resistance (A&B)	Passes - MSR - B1
ASTM D7027 Hoffman Evaluation of Scratch Resistance	Passes - 0.05mm Wide Scratch 30N
ASTM D4060 Abrasion Resistance	Passes - 10,000 cycles
ASTM F3261 Thickness Swell	Passes - 0.00%



### Environmental Data

Indoor Air Quality: This product is Assure Certified  
LEED Scoreboard: Available on request

### Warranty

30 Years Residential Surface Waterproof  
30 Years Residential Wear  
10 Years Light Commercial Wear

stantondesign.com