

STANTON

FINE HARDWOOD

Uptown 7.5" French White Oak

SPECIES	TOP LAYER	French White Oak
	CORE	Spruce
	BACK	Pine or Spruce Balancing Layer
	GRADE	Country Grade
SIZES	PLANK DIMENSION	7 1/2" x 82 5/8" (RL 24" - 82 5/8")
	THICKNESS	5/8"
	TOP LAYER	4mm Live Sawn
	CORE	9.5mm (13/32")
	BACK	1.5mm (1/16")
	EDGE	Micro Bevel, 4 Sides
CONSTRUCTION	ENGINEERED WOOD	
	FINISH	UV-cured Polyurethane, nano carbide-enhanced anti-scratch top coat, ultra-matte, 6-8 % gloss, Solvent free, 100% solid, Non-off gassing, ECO-certified
	GLUE	EPI adhesive, Free of formaldehyde, EPA compliant
APPLICATION	Floor and Wall	
INSTALLATION	Staple, Glue or Floating installation. Radiant Heat-compatible over wood or concrete subfloor	
PACKING	25.85 SF/carton – 55 cartons/pallet – 1,421.75 SF/pallet	
WARRANTY	50-Year Residential Surface Finish	
	5-Year Light Commercial Surface Finish	
	Lifetime Structural Warranty	

TESTS	EMISSIONS TEST	CA-DPH spec 01350, Prop65: Pass
	CRITICAL RADIANT FLUX	0.51 w/cm ² ASTM E 648-06. >Class 1 NFPA Life Safety Code 101, IBC 804.2
	SURFACE BURNING	F 110 – S 400 ASTM E84
	SMOKE DENSITY	Average Dmc 463 Flaming – 512 Non Flaming ASTM E 662-05
	COEFFICIENT OF FRICTION	.96 Dry Standard Neolite ASTM D 2394
	SLIP RESISTANCE	W .86 D .85 ASTM C1028
	MOISTURE CONTENT	>6% to <9% ASTM D 4442
	DELAMINATION TEST	ANSI/HPVA Bond Line Test 100% pass

GREEN BUILD STATEMENT

Uptown may also contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems EQc4, as it uses adhesives that meet the SCAQMD rule #1168 and it contains no added urea formaldehyde, as required by LEED®. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

CERTIFIED MANUFACTURING

- GREENGUARD Gold, California Prop 65 Certified
- Lacey Act Compliance
- Adhesive used in manufacturing, meet and exceed E0 standard
- No added urea formaldehyde, no halogenated hydrocarbons, herbicides, heavy metals



Elevated by design.

stantondesign.com

STANTON

FINE HARDWOOD

Hudson 7.5" French White Oak

SPECIES	TOP LAYER	French White Oak
	CORE	Spruce
	BACK	Pine or Spruce Balancing Layer
	GRADE	Prime Grade
SIZES	PLANK DIMENSION	7 1/2" x 74 7/8" (RL 24" - 74 7/8")
	THICKNESS	5/8"
	TOP LAYER	4mm Live Sawn
	CORE	9.5mm (13/32")
	BACK	1.5mm (1/16")
	EDGE	Micro Bevel, 4 Sides
CONSTRUCTION	ENGINEERED WOOD	
	FINISH	UV-cured Polyurethane, nano carbide-enhanced anti-scratch top coat, ultra-matte, 6-8 % gloss, Solvent free, 100% solid, Non-off gassing, ECO-certified
	GLUE	EPI adhesive, Free of formaldehyde, EPA compliant
APPLICATION	Floor and Wall	
INSTALLATION	Staple, Glue or Floating installation. Radiant Heat-compatible over wood or concrete subfloor	
PACKING	23.32 SF/carton – 55 cartons/pallet – 1,282.60 SF/pallet	
WARRANTY	50-Year Residential Surface Finish	
	5-Year Light Commercial Surface Finish	
	Lifetime Structural Warranty	

TESTS	EMISSIONS TEST	CA-DPH spec 01350, Prop65: Pass
	CRITICAL RADIANT FLUX	0.51 w/cm ² ASTM E 648-06. >Class 1 NFPA Life Safety Code 101, IBC 804.2
	SURFACE BURNING	F 110 – S 400 ASTM E84
	SMOKE DENSITY	Average Dmc 463 Flaming – 512 Non Flaming ASTM E 662-05
	COEFFICIENT OF FRICTION	.96 Dry Standard Neolite ASTM D 2394
	SLIP RESISTANCE	W .86 D .85 ASTM C1028
	MOISTURE CONTENT	>6% to <9% ASTM D 4442
	DELAMINATION TEST	ANSI/HPVA Bond Line Test 100% pass

GREEN BUILD STATEMENT

Hudson may also contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems EQc4, as it uses adhesives that meet the SCAQMD rule #1168 and it contains no added urea formaldehyde, as required by LEED®. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

CERTIFIED MANUFACTURING

- GREENGUARD Gold, California Prop 65 Certified
- Lacey Act Compliance
- Adhesive used in manufacturing, meet and exceed E0 standard
- **No added urea formaldehyde**, no halogenated hydrocarbons, herbicides, heavy metals



Elevated by design.

stantondesign.com

Lexington 11.25" European White Oak

SPECIES	TOP LAYER	European White Oak
	CORE	Eucalyptus/Rubberwood Plywood
	BACK	Poplar
	GRADE	Country
SIZES	PLANK DIMENSION	11 1/4" x 86 5/8" (RL 23 5/8" - 86 5/8")
	THICKNESS	3/4"
	TOP LAYER	5mm
	CORE	12.4mm (0.489")
	BACK	0.6mm (0.024")
	EDGE	Beveled, 4 sides
CONSTRUCTION	ENGINEERED WOOD	
	FINISH	UV-Cured Aluminum Oxide Polyurethane
	GLUE	MUF Glue, CARB and EPA compliant
APPLICATION	Floor and Wall	
INSTALLATION	Staple, Glue or Floating installation	
PACKING	27 SF/carton - 36 cartons/pallet - 971.85 SF/pallet	
WARRANTY	50-Year Residential Surface Finish	
	5-Year Light Commercial Surface Finish	
	Lifetime Structural Warranty	



CERTIFIED BY
SCS Global Services



STANTON

FINE HARDWOOD

Seaport 9.5" Baltic Ash

SPECIES	TOP LAYER	Baltic Ash
	CORE	Spruce
	BACK	Pine or Spruce Balancing Layer
	GRADE	Country Grade
SIZES	PLANK DIMENSION	9 1/2" x 82 5/8" (RL 24" - 82 5/8")
	THICKNESS	5/8"
	TOP LAYER	4mm Live Sawn
	CORE	9.5mm (13/32")
	BACK	1.5mm (1/16")
	EDGE	Micro Bevel, 4 Sides
CONSTRUCTION	ENGINEERED WOOD	
	FINISH	UV-cured Polyurethane, nano carbide-enhanced anti-scratch top coat, ultra-matte, 6-8 % gloss, Solvent free, 100% solid, Non-off gassing, ECO-certified
	GLUE	EPI adhesive, Free of formaldehyde, EPA compliant
APPLICATION	Floor and Wall	
INSTALLATION	Staple, Glue or Floating installation. Radiant Heat-compatible over wood or concrete subfloor	
PACKING	32.55 SF/carton – 44 cartons/pallet – 1,432.20 SF/pallet	
WARRANTY	50-Year Residential Surface Finish	
	5-Year Light Commercial Surface Finish	
	Lifetime Structural Warranty	

TESTS	EMISSIONS TEST	CA-DPH spec 01350, Prop65: Pass
	CRITICAL RADIANT FLUX	0.51 w/cm ² ASTM E 648-06. >Class 1 NFPA Life Safety Code 101, IBC 804.2
	SURFACE BURNING	F 110 – S 400 ASTM E84
	SMOKE DENSITY	Average Dmc 463 Flaming – 512 Non Flaming ASTM E 662-05
	COEFFICIENT OF FRICTION	.96 Dry Standard Neolite ASTM D 2394
	SLIP RESISTANCE	W .86 D .85 ASTM C1028
	MOISTURE CONTENT	>6% to <9% ASTM D 4442
	DELAMINATION TEST	ANSI/HPVA Bond Line Test 100% pass

GREEN BUILD STATEMENT

Seaport may also contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems EQc4, as it uses adhesives that meet the SCAQMD rule #1168 and it contains no added urea formaldehyde, as required by LEED®. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

CERTIFIED MANUFACTURING

- GREENGUARD Gold, California Prop 65 Certified
- Lacey Act Compliance
- Adhesive used in manufacturing, meet and exceed E0 standard
- **No added urea formaldehyde**, no halogenated hydrocarbons, herbicides, heavy metals



Elevated by design.

stantondesign.com

STANTON

FINE HARDWOOD

SoHo Peak Pattern Plank, French White Oak (Coordinating planks: SoHo)

SPECIES	TOP LAYER	French White Oak
	CORE	Spruce
	BACK	Pine or Spruce Balancing Layer
	GRADE	Classic Grade
SIZES	PLANK DIMENSION	4 3/4" x 23 5/8" (Fixed Length)
	THICKNESS	9/16"
	TOP LAYER	3mm Live Sawn
	CORE	9.5mm (13/32")
	BACK	1.5mm (1/16")
	EDGE	Micro Bevel, 4 Sides
CONSTRUCTION	ENGINEERED WOOD	
	FINISH	UV-cured Polyurethane, nano carbide-enhanced anti-scratch top coat, ultra-matte, 6-8 % gloss, Solvent free, 100% solid, Non-off gassing, ECO-certified
	GLUE	Phenolic Resin glue, EPA TSCH title 6 compliant
APPLICATION	Floor and Wall	
INSTALLATION	Staple, Glue or Floating installation. Radiant Heat-compatible over wood or concrete subfloor	
PACKING	10.9 SF/carton – 72 cartons/pallet – 781.20 SF/pallet	
WARRANTY	25-Year Residential Surface Finish	
	3-Year Light Commercial Surface Finish	
	Lifetime Structural Warranty	

TESTS	EMISSIONS TEST	CA-DPH spec 01350, Prop65: Pass
	CRITICAL RADIANT FLUX	0.51 w/cm ² ASTM E 648-06. >Class 1 NFPA Life Safety Code 101, IBC 804.2
	SURFACE BURNING	F 110 – S 400 ASTM E84
	SMOKE DENSITY	Average Dmc 463 Flaming – 512 Non Flaming ASTM E 662-05
	COEFFICIENT OF FRICTION	.96 Dry Standard Neolite ASTM D 2394
	SLIP RESISTANCE	W .86 D .85 ASTM C1028
	MOISTURE CONTENT	>6% to <9% ASTM D 4442
	DELAMINATION TEST	ANSI/HPVA Bond Line Test 100% pass

GREEN BUILD STATEMENT

Soho Peak may also contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems EQc4, as it uses adhesives that meet the SCAQMD rule #1168. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

CERTIFIED MANUFACTURING

- GREENGUARD Gold, California Prop 65 Certified
- Lacey Act Compliance
- Adhesive used in manufacturing, meet and exceed E0 standard.
- No halogenated hydrocarbons, herbicides, heavy metals



Elevated by design.

stantondesign.com

STANTON

FINE HARDWOOD

SoHo

6" French White Oak (Coordinating pattern plank: SoHo Peak)

SPECIES	TOP LAYER	French White Oak
	CORE	Spruce
	BACK	Pine or Spruce Balancing Layer
	GRADE	Country Grade
SIZES	PLANK DIMENSION	6" x 71" (RL 24"-71")
	THICKNESS	9/16"
	TOP LAYER	3mm Live Sawn
	CORE	9.5mm (13/32")
	BACK	1.5mm (1/16")
	EDGE	Micro Bevel, 4 Sides
CONSTRUCTION	ENGINEERED WOOD	
	FINISH	UV-cured Polyurethane, nano carbide-enhanced anti-scratch top coat, ultra-matte, 6-8 % gloss, Solvent free, 100% solid, Non-off gassing, ECO-certified
	GLUE	Phenolic Resin glue, EPA TSCH title 6 compliant
APPLICATION	Floor and Wall	
INSTALLATION	Staple, Glue or Floating installation. Radiant Heat-compatible over wood or concrete subfloor	
PACKING	23.3 SF/carton – 48 cartons/pallet – 1,116.0 SF/pallet	
WARRANTY	25-Year Residential Surface Finish	
	3-Year Light Commercial Surface Finish	
	Lifetime Structural Warranty	

TESTS	EMISSIONS TEST	CA-DPH spec 01350, Prop65: Pass
	CRITICAL RADIANT FLUX	0.51 w/cm ² ASTM E 648-06. >Class 1 NFPA Life Safety Code 101, IBC 804.2
	SURFACE BURNING	F 110 – S 400 ASTM E84
	SMOKE DENSITY	Average Dmc 463 Flaming – 512 Non Flaming ASTM E 662-05
	COEFFICIENT OF FRICTION	.96 Dry Standard Neolite ASTM D 2394
	SLIP RESISTANCE	W .86 D .85 ASTM C1028
	MOISTURE CONTENT	>6% to <9% ASTM D 4442
	DELAMINATION TEST	ANSI/HPVA Bond Line Test 100% pass

GREEN BUILD STATEMENT

SoHo may also contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems EQc4, as it uses adhesives that meet the SCAQMD rule #1168. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

CERTIFIED MANUFACTURING

- GREENGUARD Gold, California Prop 65 Certified
- Lacey Act Compliance
- Adhesive used in manufacturing, meet and exceed E0 standard.
- No halogenated hydrocarbons, herbicides, heavy metals



Elevated by design.

stantondesign.com