# STANTON

DECORATIVE | WATERPROOF SPC

# Flex Collection & Flex Collection II

Specifications	Description
Construction	Flexible LVP
Classification	ASTM F1700 Class III, Type B
Total Thickness	2.5mm
Wear Layer Thickness	20mils (0.5mm)
Wear Layer	UV-Cured Urethane
Edge Treatment	Micro Bevel on all 4 sides
Flex Collection Size	7.25" Wide x 48" Long
Packaging	Per Carton: 17 pcs. / 41.1 ft. <sup>2</sup> / 42.12 lbs. / 55 boxes per pallet / 2,259.4 ft. <sup>2</sup> per pallet
Flex Collection II Size	7" Wide x 48" Long
Packaging	Per Carton: 18 pcs. / 42 ft.² / 37.63 lbs. / 60 boxes per pallet / 2,520.05 ft.² per pallet
Installation Method	Full Spread Adhesive

### Testing

Critical Radiant Flux (ASTME648) Class 1
Surface Flammability (DOC FF 1-70) Passed
Coefficient of Friction (ASTM D2047) Passes > 0.6
Static Load Limit (ASTM F970) 1300 lbs.
Impact Insulation Class IIC = 65
Sound Transmission Class STC = 62

#### **Environmental Data**

Assure Certified Phthalate Free 100% Virgin PVC



### Warranty

Lifetime Waterproof Lifetime Residential Wear 25 Year Commercial Wear