

STANTON

100% WATERPROOF WPC

Natural Beauty Summit 10 Series Specification

STYLE: Park City, Vail Valley

Specifications

Construction	Solid WPC Core
Total Thickness	12 mm (0.55 mm Wear Layer / 2mm Topper / 8mm Waterproof WPC Core / 2mm IXPE Pad)
Wear Layer Thickness	22 mils (0.50mm)
Locking System	Unilin Uniclic
Edge Treatment	Cut Painted Bevel on 4 sides
Faces/Embossing/Gloss	5 / All-Over Emboss / 5-8%
Size	10" Wide x 82" Long
Packaging	Per Carton: 5 pcs / 28.47 ft. ² / 66.47 lbs. / 40 boxes per pallet / 1,138.89 ft. ² per pallet
Installation Method	Floating / Glue Down
Expansion and Transitions Required	½" expansion and relief against all vertical obstructions
Waterproofing Wet Areas	½" expansion space/use ½" foam backer rod and 100% silicone filled in all expansion gaps, and transitions. With this product no floor drains are allowed
Radiant Floor	Installation Approved Over Embedded Systems Only

Description

Material Classification:

Test Methods	Results
ASTM F2199 Dimensional Stability W/L	W0.04%-0.05%/L0.08%-0.12%
ASTM F2199 Dimensional Stability Curling/Bowing	≤1mm
ASTM F2055 Squareness	≤0.25mm
ASTM F1914 Residual Indentation	0.05mm
ASTM F970-17 Static Load	0.1mm
ASTM E648 Flooring Radiant Panel	≤450
ASTM D2047 Slip Resistance	Dry 0.75
ASTM E492 Acoustic IIC	64dB
ASTM E90 Acoustic STC	64dB
ASTM F1515 Resistance to Light	ΔE≤2
ASTM F925 Chemical Resistance	rating 0
ASTM F1514 Resistance to Heat	ΔE≤0.5

Environmental Data

Indoor Air Quality
LEED Scoreboard

Description

This product is Assure Certified
Available on request



Warranty

Lifetime Surface Waterproof
Limited Lifetime Residential
10-Year Medium Commercial