

STANTON

100% WATERPROOF WPC

Natural Beauty Lux 9XL Series Specification

STYLE: Bristol Point

Specifications

Specifications	Description
Construction	Solid WPC Core
Total Thickness	10mm (0.55mm Wear Layer / 2mm Topper/6mm Waterproof WPC Core / 2mm IXPE Pad)
Wear Layer Thickness	22 mils (0.50mm)
Locking System	Unilin Uniclic
Edge Treatment	Pressed Bevel on 4 sides
Faces/Embossing/Gloss	5 / EIR / 4-6%
Size	9" Wide x 72" Long
Packaging	Per Carton: 7 pcs / 31.00 ft. ² / 61.60 lbs. / 44 boxes per pallet / 1,363.87 ft. ² per pallet
Installation Method	Floating / Glue Down
Expansion and Transitions Required	¼" expansion and relief against all vertical obstructions. Installation exceeding ½" expansion and relief against all vertical obstructions.
Waterproofing Wet Areas	½" expansion space/use ½" foam backer rod and 100% silicone filled in all expansion gaps, and transitions. With this product no floor drains are allowed
Radiant Floor	Installation Approved Over Embedded Systems Only

Material Classification:

Test Methods	Results
ASTM F2199 Dimensional Stability W/L	≤0.2%
ASTM F2199 Dimensional Stability Curling/Bowing	≤2mm
ASTM F2055 Squareness	≤0.25mm
ASTM F1914 Residual Indentation	≤0.18mm
ASTM F970-17 Static Load	≤0.13mm
ASTM E648 Flooring Radiant Panel	Class 1
ASTM D2047 Slip Resistance	> 0.5
ASTM E492 Acoustic IIC	60
ASTM E90 Acoustic STC	65
ASTM F1515 Resistance to Light	ΔE* < 8
ASTM F925 Chemical Resistance	Rating 0
ASTM F1514 Resistance to Heat	ΔE* < 8

Environmental Data

Indoor Air Quality
LEED Scoreboard

Description

This product is Assure Certified
Available on request



Warranty

Lifetime Surface Waterproof
Limited Lifetime Residential
10-Year Medium Commercial