



DATA SHEET

1100 Cross Piece Grille


Solid Wood



1100 | CROSS PIECE GRILLE | SOLID WOOD

The **9Wood Cross Piece Grille** wood ceiling offers a design where the individual wood member is deeper than it is wide. The solid wood panel width is 12", with lengths ranging from 2' to 12' in 1' increments.


Attachment for the **Cross Piece Grille** is via screws fastened directly through the backer into standard T-Bar grid. This provides basic accessibility for each panel.




CROSS PIECE GRILLE | Typical Specifications



Typical Specifications



Suspension Conditions



CROSS PIECE GRILLE | SKU Table



How to build your SKU

- **Pick your member size** (Rows). This gives you your first four digits (e.g., 1112).
- **Pick your density** (Columns). This is the number of wood members per foot.
- **Combine them with a dash**. A 1x2 member with 8 members per foot creates SKU 1112-8.

SKU Decoder

- Style "1100 Cross Piece Grille"
- Nominal Width "1 x 2 Nominal"
- Nominal Length "8 Members / LF"

Example:

11 12 - 8
11 XX - X
XX 12 - X
XXXX - 8

SKU Table

Member Size (Nominal)	Width	Depth	Density (Members per Linear Foot)							
			2	3	4	5	6	7	8	
1 x 2	3/4"	1 3/8"	1112-2	1112-3	1112-4	1112-5	1112-6	1112-7	1112-8	
1 x 3	3/4"	2 1/4"	1113-2	1113-3	1113-4	1113-5	1113-6	1113-7	1113-8	
1 x 4	3/4"	3 1/4"	1114-2	1114-3	1114-4	1114-5	1114-6	1114-7	1114-8	
1 x 6	3/4"	5 1/4"	1116-2	1116-3	1116-4	1116-5				
2 x 3	1 3/8"	2 1/4"	1123-2	1123-3	1123-4	1123-5	1123-6			
2 x 4	1 3/8"	3 1/4"	1124-2	1124-3	1124-4	1124-5				

Additional width, depth, and M/LF options may be available.
Please check with 9Wood if you don't see the combination that you have in mind.


CROSS PIECE GRILLE | Lighting Integration Guidance




Key Points

- All fixtures **must** be independently supported.
- Cut panels may require supplemental reinforcement.
- 9Wood is here to help

Downlight Examples




Direct Mount to T-Bar options use clips or brackets to attach lighting fixtures securely. Cut panels may require supplemental reinforcement.




Integrate Downlights, cut precise openings in slats and add trim rings for downlights when cutting slats.

Linear Lighting Examples



Fixtures must be independently supported. Lighting is always mounted to structure or T-Bar, not to wood members or clips.



Integrate Linear Lighting by running fixtures parallel to the wood slats and coordinating dimensions with the slat reveals.

SPECIES OPTIONS | Solid Wood



Species Options

Custom Made Fast is available in three solid wood species. Mixed Grain Western Hemlock is recommended for most applications due to its cost efficiency, versatility, and visual consistency. White Oak is available only in 1x2 and 1x3 members. Certified Douglas Fir availability is limited and subject to market volatility.



Western Hemlock
Mixed Grain

Finish & Color Options

All products are finished with a clear matte topcoat, regardless of stain color. Standard stain colors are available with Western Hemlock. Custom Color Matching is always available with no required minimums and at the same cost as Standard options. Send 9Wood a control sample to get started.



Western Hemlock
Vertical Grain



White Oak
Mixed Grain



Douglas Fir
Mixed Grain



Application

The Cross Piece Grille uses a pre-assembled panel fabrication process. This product can be installed throughout the country and is the preferred design in areas requiring seismic compliance. Panel access is available by means of removing attachment screws hidden in reveals. Repeated removal requires threaded 9Wood Caddy-Lock attachment as opposed to screws.

Acclimatization

Cross Piece Grilles must be cared for in a controlled interior environment (RH 25%-55% max; temp. 60°-80°) and installed only after reaching equilibrium moisture content.

Acoustics

The Cross Piece Grille can enhance acoustics via sound absorbing material placed over open reveals within the T-Bar grid. Insulation is typically provided locally. Specifiers should search within CSI MasterFormat Division 09 and Division 23, including:

09 81 00 Acoustical Insulation

09 84 00 Acoustical Wall/Ceiling Elements

23 07 00 HVAC Insulation

Fire Rating

Individual members are treated with a Fire Retardant that helps it meet Class A per ASTM E84.

LEED

Cross Piece Grilles may help contribute to LEED credits for: Material sourcing, Material ingredients, Low Emitting Materials, and Environmental Product Declarations. Credit support based on design choices.

MEP

The Cross Piece Grille permits MEP penetrations in the ceiling's surface. Cut panels may require supplemental reinforcement. Fixtures and diffusers must be independently supported.

Seismic

Cross Piece Grilles provide seismic code compliance by means of mechanical direct screw attachment to T-Bar via the cross piece backer. Please consult local code or a licensed engineer for any additional requirements.

Suspension

Cross Piece Grilles are directly attached to 15/16" heavy duty T-Bar main runners. Main runners are installed 2' on center, depending on panel weight.

System Weight

Cross Piece Grilles typically weigh 2-4 pounds per square foot, depending on members per linear foot and species.



Custom
made fast

9wood.com

999 South A Street
Springfield, OR 97477
Tel: 888-767-9990
sales@9wood.com

This information is for illustrative purposes only.
The featured products and processes are specific
to the project and should not be duplicated
without consulting 9Wood. © 2026 9Wood

January 2026