



OPX 1025

Optical PM Mass Monitor

The **OPX 1025** is a continuous particulate matter (PM) monitor using optical particle spectrometer technology with a polychromatic light source. It measures and records PM concentrations (e.g., $PM_{2.5}$, PM_{10}) by analyzing particle size and count from scattered light signatures and applying the proprietary RealPM size/density mass conversion algorithm, which automatically accounts for environmental factors.

Ambient air is drawn at a controlled flow rate through a size-selective (or optional TSP) inlet, conditioned via a Smart Heater, and analyzed in real-time, providing accurate, low maintenance mass concentration data.

Key features

- **Advanced Optical Particle Spectrometer**

Polychromatic light source with 4,096 raw size bins, combined into 100 bins for mass conversion.

- **RealPM Dynamic Mass Conversion Algorithm**

Size/density algorithm designed for high accuracy across varying environmental conditions.

- **Comprehensive PM Reporting**

Simultaneous real-time PM_{10} , $PM_{2.5}$, PM_4 , PM_{10} , and coarse fraction ($PM_{10-2.5}$) plus particle count and size histograms.

- **Controlled Sampling System**

PM_{10} or TSP inlet, 16.67 LPM flow control, Smart Heater for humidity/temperature conditioning, and sheath flow optics protection.

- **High Sensitivity**

Greater sensitivity than traditional continuous PM mass monitor methods.

- **User-Friendly Operation**

Intuitive touchscreen interface with advanced diagnostics for quick troubleshooting.

- **Advanced Communications**

Remote operation capability with cloud-based data access and integration with meteorological and other sensors.

- **Precision Calibration**

Factory-calibrated against reference units; size accuracy verified with PSL and SigmaDust standards.

- **Low Maintenance**

Minimal consumables required, and sheath-flow over optics reduces cleaning intervals.

- **Produced by an industry-leading ISO Certified facility.**


- **Time-tested reliability backed up by a 2-year Warranty.**

- **Sensor LED backed by 10-year manufacturer's warranty (parts only, field replaceable)**

Applications

- Ambient air quality monitoring ($PM_{2.5}$, PM_{10})
- Industrial and emissions monitoring
- Construction and mining site dust control
- Roadside and traffic pollution studies
- Fence-line and community monitoring
- Research and environmental studies
- Indoor air quality assessments
- Mobile or temporary monitoring campaigns





Specifications	
Measurement Principle	Broadband spectroscopy using 85°–95° light scattering with polychromatic LED
Particle Size Resolution	0.18 – 24µm range over 100 sizing channels
PM Mass Measurements	PM ₁₀ , PM _{2.5} , PM _{10–2.5} , as well as PM ₄ , PM ₁ , and TSP*
PM Mass Measurement Range	0.0 – 10,000+ µg/m ³
Data Display Resolution	0.1 µg/m ³
Lower Detectable Limit	< 0.1 µg/m ³
Measurement Interval	10 seconds
Averaging Periods	User Adjustable: 1m – 24hr
Mass Concentration Accuracy	Meets or Exceeds US EPA PM ₁₀ FEM and Class III PM _{2.5} & PM _{10–2.5} FEM performance requirements compared to FRM samplers
Flow Rate	16.67 lpm
Flow Accuracy	±1% (Typically within ±0.5%)
Operating Temperature	0 – 50°C (inside shelter/enclosure)
Ambient Sample Temperature	–40 – 60°C
Ambient Sample Relative Humidity	0 – 100%
Sample RH Control	24VDC 150W (max) heater controlled to 35% RH or lower
Enclosure / Shelter	Requires weatherproof enclosure/shelter with 0–50°C, non-condensing environmental control
Instrument Warm-up Time	< 5 minutes
User Interface	Large graphic touchscreen display with intuitive layout / menu structure, and remote interface

Specifications	
Internal Data Storage	1 year of internal data storage, including all PM values, peripheral measurements, and size histograms
Data Download	Two Front Panel USB Flash Drive Ports (1xUSB-A and 1xUSB-C), and Ethernet and serial ports on rear panel
Ambient Sensor	Model BX-597A combination Temperature/Pressure/RH sensor
Optional Sensor Inputs	Smart Sensor inputs such as digital wind speed and direction (i.e. Met One Model AIO 2)
Electrical	100 - 240 VAC, 50/60Hz; 190W (max) power consumption, 50W typical
Instrument Dimensions (HxWxD)	26.7cm x 43cm x 40cm (10.5" x 17" x 15.8")
Instrument Weight	31 lbs (14 kg)
Sample Conditioner Dimensions	88.6cm x 6.35cm (34.875" x 2.5")
Sample Conditioner Weight	4.2 lbs (1.9 kg)
Warranty	2-year standard instrument warranty 10-year manufacturer's warranty on sensor LED [^]
Certifications	US EPA Class III PM _{2.5} Federal Equivalent Method (EQPM-1125-273) US EPA PM ₁₀ Federal Equivalent Method (EQPM-1225-274) US EPA Class III PM _{10-2.5} Federal Equivalent Method (EQPM-1225-275)

*Using optional TSP inlet; ^ parts only, field replaceable

Supplied Accessories

- Sigmadust
- **BX-597A** Temperature/RH/Pressure Sensor
- Operation manual
- Calibration certificate
- Quick start guide

Optional Accessories

- **BX-801** Sample Inlet System with Support Braces
- TSP Inlet
- AIO 2 Weather Station
- **BX-925B** Weatherproof Enclosure with Heater
- **BX-925B-AC** Weatherproof Enclosure with Heater and Air Conditioner
- **BX-802** PM₁₀ Inlet



POWERED BY ACOEM

Specifications subject to change without notice. Images used are for illustrative purposes only. All trademarks and registered trademarks are the property of their respective owners.

© 2025 Acoem and all related entities. All rights reserved. 20250911

metone.com