



MicroVol™ 1100

Low Volume Air Sampler

The Acoem MicroVol 1100* low volume air sampler provides a flexible sampling platform for PM₁₀, PM_{2.5} or TSP particulates and basic meteorological parameters.

It is suitable for both indoor and outdoor applications. The unit is microprocessor controlled and uses a mass flow sensor in conjunction with ambient temperature and pressure sensors to automatically maintain a constant volumetric flow rate.

* Acoem MicroVol 1100 formerly known as Ecotech MicroVol 1100.

Measurements consistent with*

- PM₁₀ AS 3580.9.9 2017

* Keywood et al. (2000) CSIRO Atmospheric Research, 'Testing a low-cost aerosol sampler', Clean Air and Environmental Quality, Vol 34 No 4, pp. 38-42.

Indoor sampling

- Low power consumption
 - Quiet operation – ideal for indoor air quality studies
 - Volumetric flow control automatically corrected to standard reference temperature
 - Ultra-efficient, long life DC pump delivers flow rates of 1.0 to 4.5 L/min.
-

Outdoor sampling

- Wind direction & speed used to activate/deactivate sampler
 - Fence line monitoring available with a network of samplers
 - Built for all conditions – lightweight, rugged weatherproof construction
 - Can operate via battery or solar powered sources (optional).
-

Enhanced communication

- RS232 output for data collection & remote communication
 - Filter block & instrument error alarms available
 - Total control of instrument remotely from PC
 - Simple programming of sampling periods, including daily & weekly programs, with in built “1-in-X day” sampling capability.
-

Directional sampling

- Wind direction & speed used to activate/deactivate sampler
- External trigger (0 – 5 VDC) can be used for activating sampling program.

Specifications

| | |
|--|--|
| Operation: | Microprocessor controlled (internal data logging) |
| Volumetric flow range/accuracy: | 1.0 - 4.5 L/m |
| Flow accuracy: | ± 2 % of reading |
| Flow repeatability: | ± 0.5 % of reading |
| Temperature range accuracy: | 0 - 45 °C ± 1 °C |
| Barometric pressure range: | 600 - 900 Torr ± 4 Torr |
| Filter types: | 47 mm ringed circular filter |
| Inlets available: | PM ₁₀ , TSP (standard), PM _{2.5} (optional) |
| Sampler dimensions: | 300 x 170 x 170 mm |
| Sampler weight: | 3.75 kg |
| Battery pack dimensions: | 185 x 170 x 170 mm |
| Battery pack weight: | 4.4 kg |
| Battery pack life: | Up to 40 hours sampling from fully charged battery pack |
| Operating voltage: | 12 VDC |
| Power consumption: | 2.5 - 3 watts depending on filter loading |
| Standard accessories: | TSP/PM ₁₀ size selective inlet Single 47 mm filter holder 100 - 240 AC to 12 VDC power converter MicroVol downloader software RS232 cable |

Communication & data logging

Number of readings

- 150 (averaging period is user selectable, e.g. 75 hrs of 30 min averages)

External inputs

- 1 x wind direction sensor input (10 k potentiometer)
- 1 x wind speed sensor input (contact closure)
- 1 x spare contact closure input (e.g. tipping bucket rain gauge)

Output

- RS232C

Options

- Purpose built battery pack, or solar panel & battery pack
- Moisture elimination system
- Optional PM_{2.5} size selective inlet adaptor
- Optional wind speed & direction sensor or tipping bucket rain gauge.

