ASPIRO® SERIES Exterior Application Paintable – Stile & Rail



ŢĘ.	Door Styles (Panel Styles may vary based on required construction)	French, Traditional, Archtop (radius), Other
STYLE	Panel Design (Panel Styles may vary based on required construction)	Square-top, Archtop (radius) panels, Eyebrow, Provence, Other
DIMENSIONS	Single Doors (max size listed) Consult factory for oversized doors.	Width: 42" Height: 96" Thickness: 1-3/4", 2-1/4"
	Pair Doors (max size listed) (Standard Swinging, Contact Factory for D/E)	Width: 84" Height: 96" Thickness: 1-3/4", 2-1/4"
	Default Face Dimensions Contact factory for custom options	 Stiles: 5-1/2" Top Rail: 5-1/2" Bottom Rail: 10" (minimum 12" for over 36" wide) Lock Rail: 6-1/2" Muntins (Simulated Divided Lite) & Bars (True Divided Lite): 1-3/8" (including glass stops) Crossrail (Intermediate): 3-5/8" Mullions: 3-5/8"
CONSTRUCTION	Surface Material Expansive veneer offerings available. Contact factory for details.	Painted: Stiles and Rails - Mahogany, Panels MDF
	Joinery	Cope & Stick; Doweled
	Core and Panel Material	 Stiles: SCLC Top Rail: Solid Lumber Bottom Rail: Solid Lumber Lock Rail: Solid Lumber Mid-rails: Solid Lumber Mullions: Solid Lumber Louvers (Standard, False, Chevron): Solid Lumber (no warranty) Raised Panel: MDF Veneer Wrapped Raised Panel: N/A Flat Panel: MDF Paint Grade Panel/False Louvers: Solid Wood
	Panel Options	 Raised Panel: 1-5/8" Veneer Wrapped Raised Panel: N/A Flat Panel: 5/8" V-Groove Flat Panel: 1-1/8" V-Groove Raised Panel: 1-5/8"

ASPIRO® SERIES Exterior Application Paintable – Stile & Rail



CONSTRUCTION	Sticking Options	Ogee, Ovolo, No profile,
	Contact factory for custom options.	Square, Quarter Round, Custom
	Raised and Applied Moulding	Available upon request
	Glass	Standard Glass (Maximum cutout): -1/4" Tempered -5/8" Tempered insulated Optional Glass Types: -Tempered: Clear, Clear Bevel, Acid Etched, Acid Etched with Clear Bevel -Laminated: Clear, White Contact factory for options and limitations. Additional Options: Insulated Glass, Low E and Argon
	Machining (Typical factory machining) Contact factory for more options.	 Hinges Cylindrical locks Mortise locks with or without function holes Card Locks Exit devices Automatic or Manual flush bolts Concealed overhead closers/stops Door bottoms Electric Strikes Viewers Wire Raceways EPT's
CREDITS	Environmental Options (available upon request)	Recycled Content Certified Wood Low-Emitting Materials CARB Phase II Compliant
STC	Acoustic Rating	N/A
	Warranty	3 Year Warranty (must be factory finished)
	Label Agency	N/A