

CENDURA® SERIES

Fire-Resistant Mineral Core 45 - 90 Min /  
Bonded Construction  
High Pressure Decorative Laminate



	<b>Models</b>	A-MC-B-FR45 A-MC-B-FR60 A-MC-B-FR90			
<b>DIMENSIONS</b>	<b>Thickness</b>	1-3/4"			
	<b>Maximum Size</b>	ITS-WH AND UL Sizes noted in this table are specific to 1-3/4" doors. Contact sales for information regarding other door thickness types.			
			Neutral Pressure	CAT A Positive Pressure	CAT B Positive Pressure
		Singles	4'0"x9'0"	4'0"x9'0"	4'0"x9'0"
		Pairs	8'0"x9'0"	8'0"x9'0"	8'0"x9'0"
DE Pairs	8'0"x8'0"	8'0"x8'0"	8'0"x8'0"		
<b>CONSTRUCTION</b>	<b>Surface Material</b>	High Pressure Decorative Laminate			
	<b>Crossbands</b>	One Piece High Density Fiberboard (HDF)			
	<b>Vertical Edges*</b>	Default: HPDL Edge Band applied after faces over Hardwood Composite Fire Stile Alternate Stile Options Upon Request: - Hardwood composite fire stile			
	<b>Horizontal Edges*</b>	Manufacturer's standard construction			
	<b>Face &amp; Core Assembly Adhesive</b>	Type 1			
	<b>Core Construction</b>	Mineral Core			
	<b>Lite Openings / Louvers</b>	- Factory glazing recommended - max 5/16" glass thickness - Available with standard veneer wrap bead, standard metal vision frames - Metal fusible link louvers also available			
	<b>Distance from Lock &amp; Lite Cutouts</b>	3-1/4" minimum distance from adjacent lock and lite cutouts			
	<b>Details</b>	N/A			
	<b>Machining</b>	Machining preparation per hardware manufacturer's templates. Some limitations apply.			
	<b>Factory Finish</b>	Wood accessories available as painted or stained			
<b>STC</b>	<b>Acoustic Rating†</b>	STC 30 Operable when installed with tested seals and gaskets - Refer to Appendix M			
<b>CREDITS &amp; STANDARDS</b>	<b>Environmental Options</b>	CARB PH2/TSCA Title VI Compliant - ULEF/NAUF* upon request - FSC upon request			
	<b>Environmental Product Declaration</b>	Yes			
	<b>Quality Standards</b>	- WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)			
	<b>WDMA Performance Duty Level†</b>	- Mineral Core without Blocking - Below Standard - Mineral Core with Blocking - Extra Heavy Duty - (Blocking for mineral core doors provided upon request)			
<b>WT.</b>	<b>Door Weight</b>	Thickness	lbs/sf		
		1-3/4"	3.7		
	<b>Warranty</b>	Limited Lifetime. No exterior warranty. Interior use only.			

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

\* Fire-Rated doors will be constructed per label service listing and may deviate from above.

† Performance Duty Level and STC Ratings are based on 1-3/4" doors.

\*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.