ASPIRO® SERIES Exterior Application Wood Veneer



STYLE	Door Styles (Panel Styles may vary based on required construction)	French, Traditional, Archtop (radius), Other
	Panel Design (Panel Styles may vary based on required construction)	Square-top, Archtop (radius) panels, Eyebrow, Provence, Other
DIMENSIONS	Single Doors (max size listed) Consult factory for oversized doors.	Width: 42" Height: 96" Thickness: 1-3/4", 2-1/4"
	Pair Doors (max size listed) (Standard Swinging, Contact Factory for D/E)	Width: 84" Height: 96" Thickness: 1-3/4", 2-1/4"
	Default Face Dimensions Contact factory for custom options	 Stiles: 5-1/2" Top Rail: 5-1/2" Bottom Rail: 10" (minimum 12" for over 36" wide) Lock Rail: 6-1/2" Muntins (Simulated Divided Lite) & Bars (True Divided Lite): 1-3/8" (including glass stops) Crossrail (Intermediate): 3-5/8" Mullions: 3-5/8"
	Surface Material	Wood Veneer: Standard 1/8"; Mahogany, Cherry, Walnut, Pine, White Oak
	Joinery	Cope & Stick; Doweled
CONSTRUCTION	Core and Panel Material	 Stiles: SCLC Top Rail: Solid Lumber Bottom Rail: Solid Lumber Lock Rail: Solid Lumber Mid-rails: Solid Lumber Mullions: Solid Lumber Louvers (Standard, False, Chevron): Solid Lumber (no warranty) Rim Banded Raised Panel: MDF Veneer Wrapped Raised Panel: N/A Flat Panel: MDF False Louvers: Solid Wood
	Panel Options	 Rim Banded Raised Panel: 1-5/8" Veneer Wrapped Raised Panel: N/A Flat Panel: 5/8" V-Groove Flat Panel: 1-1/8" V-Groove Raised Panel: 1-5/8"

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice. Fire-Rated doors will be constructed per label service listing and may deviate from above.

ASPIRO® SERIES Exterior Application Wood Veneer



CONSTRUCTION	Sticking Options Contact factory for custom options.	Ogee, Ovolo, No profile, Square, Quarter Round, Custom
	Raised and Applied Moulding	Available upon request
	Glass	 Standard Glass (Maximum cutout): -1/4" Tempered -5/8" Tempered insulated Optional Glass Types: Tempered: Clear, Clear Bevel, Acid Etched, Acid Etched with Clear Bevel Laminated: Clear, White Contact factory for options and limitations. Additional Options: Insulated Glass, Low E and Argon
	Machining (Typical factory machining) Contact factory for more options.	 Hinges Cylindrical locks Mortise locks with or without function holes Card Locks Exit devices Automatic or Manual flush bolts Concealed overhead closers / stops Door bottoms Electric Strikes Viewers Wire Raceways EPT's
CREDITS	Environmental Options (available upon request)	 Recycled Content Certified Wood Low-Emitting Materials CARB Phase II Compliant
STC	Acoustic Rating	N/A
	Warranty	3 Year Warranty (must be factory finished)
	Label Agency	N/A

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice. Fire-Rated doors will be constructed per label service listing and may deviate from above.