

# Premium Paintable Doors

## ASPIRO® SERIES

Mineral Core 45 - 60 Min  
Radiation Shielded  
Medium Density Overlay



	<b>Models</b>	A-MC-B-XR-FR45 A-MC-B-XR-FR60					
<b>DIMENSIONS</b>	<b>Product Specifications</b>	Mineral core with lead					
	<b>Thickness</b>	1-3/4"					
	<b>Lead Thickness</b>	1/32", 1/16", 1/8"					
	<b>Lead Location</b>	One sheet, narrow side (Review hardware applications when ordering)					
	<b>Maximum Size</b>	Single: 4'0"x8'0" Standard Pairs: 8'0"x8'0"					
<b>FIRE</b>	<b>Label Agency</b>	ITS-WH and UL					
	<b>Fire Rating</b>	45-60 Minute					
<b>CONSTRUCTION</b>	<b>Surface Material</b>	Medium Density Overlay					
	<b>Crossbands</b>	One Piece High Density Fiberboard (HDF)					
	<b>Vertical Edges*</b>	Hardwood Composite Fire Stile Alternate Stile Options Upon Request: - Impact resistant edges					
	<b>Horizontal Edges*</b>	Manufacturer's standard construction Alternate Rail Options Upon Request: - Clean edge					
	<b>Astragal at Pairs</b>	Lead-lined Metal Edge & Astragal					
	<b>Face &amp; Core Assembly Adhesive</b>	Type 1					
	<b>Details</b>	N/A					
	<b>Core Construction</b>	Mineral core with lead					
	<b>Lite Openings</b>	Metal Vision Frames Only - Refer to Appendix N					
	<b>Factory Finish</b>	Prime, standard and custom paint colors					
<b>STC</b>	<b>Acoustic Rating</b>	N/A					
<b>CREDITS &amp; STANDARDS</b>	<b>Environmental Options</b>	- CARB PH2/TSCA Title VI Compliant - ULEF/NAUF* upon request - FSC upon request					
	<b>Environmental Product Declaration</b>	Yes					
	<b>Quality Standards</b>	- WDMA I.S.1A Architectural Wood Flush Doors (Standard Construction) - AWS available upon request					
	<b>WDMA Performance Duty Level</b>	N/A					
<b>WT.</b>	<b>Door Weight</b>	Thickness	lbs/sf	Thickness	lbs/sf	Thickness	lbs/sf
		1/32" lead	5.8	1/16" lead	7.8	1/8" lead	13.8
	<b>Warranty</b>	Full; life of original installation. No exterior warranty. Interior use only.					

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.  
\*Fire-Rated doors will be constructed per label service listing and may deviate from above.

\*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.