

## Packaging and Weights

**Packaging\***

Doors are palletized in quantities determined by the number ordered and size. Stretch wrapping, sheet corrugated cardboard and banding are combined to give you superior packaging to protect your doors. For an additional cost, doors may be individually protected with polywrap cardboard cartons and specially packaged for jobsite delivery and coordination. When delivered by common carrier, doors are packaged using specially reinforced materials.

Bottom board palletizing is available. When selecting the bottom board palletizing service, Forte™ Opening Solutions will add a 7/16" Oriented Strand Board (OSB) to the bottom of the door pallet, offering an extra layer of protection.

**Weights**

Approximate weights per square foot by door type

Door Thickness	Door Core Type	Door Weight lbs/sf
1-3/8"	Wood Based Particleboard	4.9
1-3/4"	Wood Based Particleboard	6.0
1-3/4"	EHD Wood Based Particleboard	6.5
1-3/8"	Structural Composite Lumber	5.2
1-3/4"	Structural Composite Lumber	6.5
2"	Structural Composite Lumber	7.8
2-1/4"	Structural Composite Lumber	8.8
1-3/4"	45m Wood Based Particleboard	6.4
1-3/4"	Mineral Core	3.7
1-3/8"	Medium Density Fiberboard	4.8
1-3/4"	Medium Density Fiberboard	6.1
1-3/4"	Particleboard w/1/32" Lead	7.7
1-3/4"	Particleboard w/1/16" Lead	9.2
1-3/4"	Particleboard w/1/8" Lead	13
1-3/4"	Structural Composite Lumber w/1/32" Lead	9.1
1-3/4"	Structural Composite Lumber w/1/16" Lead	11.1
1-3/4"	Structural Composite Lumber w/1/8" Lead	15.1
1-3/8"	Hollow Core	1.3
1-3/4"	Hollow Core	1.7