

Standard Painted Doors

CENDURA® SERIES

Structural Composite Lumber Core Non-Rated & 20 Min / Bonded Construction Paint Grade Birch



	Models	C-SCLC-B-NR C-SCLC-B-FR20				
DIMENSIONS	Thickness	1-3/8", 1-3/4"				
	Maximum Size	ITS-WH and UL- Max 20 Minute Sizes noted in this table are specific to 1-3/4" doors. Contact sales for information regarding other door thickness types.				
			Non-Rated	Neutral Pressure	CAT A Positive Pressure	CAT B Positive Pressure
		Singles	4'0"x9'0"	4'0"x9'0"	4'0"x9'0"	4'0"x9'0"
		Pairs	8'0"x9'0"	8'0"x9'0"	8'0"x9'0"	8'0"x9'0"
DE Pairs	8'0"x9'0"	8'0"x9'0"	8'0"x9'0"	8'0"x9'0"		
CONSTRUCTION	Surface Material	Paint Grade Birch				
	Crossbands	One Piece High Density Fiberboard (HDF)				
	Vertical Edges*	Default: Finger-Jointed Softwood /Mill Option Low Density Hardwood Alternate Stile Options Upon Request: Full Length Mill Option/Low Density Hardwood (1.281 before trim)				
	Horizontal Edges*	Default: Structural Composite Lumber (1-1/4" before trim) No alternate rail options available.				
	Face & Core Assembly Adhesive	Type 1				
	Core Construction	Structural Composite Lumber				
	Lite Openings / Louvers	- Factory glazing recommended - max 5/16" glass - Available with standard profile wood beads or standard metal vision frames - Standard wood and metal louvers in non-rated doors only				
	Distance from Lock & Lite Cutouts	1-1/16" minimum distance from adjacent lock and lite cutouts (Non rated and 20 Minute without hose stream) 1-1/4" minimum distance from adjacent lock and lite cutouts (20 Minute with hose stream)				
	Details	Standard and custom profiles of applied mouldings				
	Machining	Machining preparation per hardware manufacturer's templates				
	Factory Finish	Prime only				
STC	Acoustic Rating†	STC 32 Operable when installed with tested seals and gaskets - Refer to Appendix M				
CREDITS & STANDARDS	Environmental Options	- CARB PH2/TSCA Title VI Compliant - ULEF/NAUF* upon request - FSC upon request				
	Environmental Product Declaration	Yes				
	Quality Standards	WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)				
	WDMA Performance Duty Level†	Extra Heavy Duty				
WT.	Door Weight	Thickness	lbs/sf	Thickness	lbs/sf	
		1-3/8"	5.2	1-3/4"	6.5	
	Warranty	Limited Lifetime. No exterior warranty. Interior use only.				

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

* Fire-Rated doors will be constructed per label service listing and may deviate from above.

† Performance Duty Level and STC Ratings are based on 1-3/4" doors.

*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.