

Standard Painted Doors

CENDURA® SERIES

Particleboard Core Non-Rated & 20 Min / Bonded Construction

Paint Grade Birch



	Models	C-MC-B-FR45 C-MC-B-FR60 C-MC-B-FR90						
DIMENSIONS	Thickness	1-3/4"						
	Maximum Size	ITS-WH and UL Sizes noted in this table are specific to 1-3/4" doors. Contact sales for information regarding other door thickness types.						
			Neutral Pressure	CAT A Positive Pressure	CAT B Positive Pressure			
		Singles	4'0"x9'0"	4'0"x9'0"	4'0"x9'0"			
		Pairs	8'0"x9'0"	8'0"x9'0"	8'0"x9'0"			
DE Pairs	8'0"x8'0"	8'0"x8'0"	8'0"x8'0"					
CONSTRUCTION	Surface Material	Paint Grade Birch						
	Crossbands	One Piece High Density Fiberboard (HDF)						
	Vertical Edges*	Default: Hardwood Composite Fire Stile						
	Horizontal Edges*	Manufacturer's standard construction						
	Face & Core Assembly Adhesive	Type 1						
	Core Construction	Mineral Core						
	Lite Openings / Louvers	<ul style="list-style-type: none"> - Factory glazing recommended - max 5/16" glass thickness - Standard veneer wrap bead, standard metal vision frames - Standard fusible link door louver 						
	Distance from Lock & Lite Cutouts	3-1/4" minimum distance from adjacent lock and lite cutouts						
	Details	Standard and custom applied moulding profiles. Some limitations apply.						
	Machining	Machining preparation per hardware manufacturer's templates. Some limitations apply.						
Factory Finish	Prime only							
STC	Acoustic Rating†	STC 30 Operable when installed with tested seals and gaskets - Refer to Appendix M						
CREDITS & STANDARDS	Environmental Options	<ul style="list-style-type: none"> - CARB PH2/TSCA Title VI Compliant - ULEF/NAUF* upon request - FSC upon request 						
	Environmental Product Declaration	Yes						
	Quality Standards	WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)						
	WDMA Performance Duty Level†	<ul style="list-style-type: none"> - Mineral Core without Blocking - Below Standard - Mineral Core with Blocking - Extra Heavy Duty - (Blocking for mineral core doors provided upon request) 						
WT.	Door Weight	<table border="1"> <tr> <th>Thickness</th> <th>lbs/sf</th> </tr> <tr> <td>1-3/4"</td> <td>3.7</td> </tr> </table>	Thickness	lbs/sf	1-3/4"	3.7		
Thickness	lbs/sf							
1-3/4"	3.7							
	Warranty	Limited Lifetime. No exterior warranty. Interior use only.						

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

* Fire-Rated doors will be constructed per label service listing and may deviate from above.

† Performance Duty Level and STC Ratings are based on 1-3/4" doors.

*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.