

Standard Painted Doors

CENDURA® SERIES 45 - 60 Min Mineral Core-Bonded Construction Molded Panel



	Models	C-MC-B-MP-FR45 C-MC-B-MP-FR60			
DIMENSIONS	Thickness	1-3/4" (2-panel designs only)			
	Maximum Size	ITS-WH only Sizes noted in this table are specific to 1-3/4" doors. Contact sales for information regarding other door thickness types.			
			Neutral Pressure	CAT A Positive Pressure	CAT B Positive Pressure
		Singles	3'0"x8'0"	3'0"x8'0"	3'0"x8'0"
Pairs		6'0"x8'0"	6'0"x8'0"	6'0"x8'0"	
	DE Pairs	N/A	N/A	N/A	
CONSTRUCTION	Surface Material	Molded Panel			
	Crossbands	N/A			
	Vertical Edges*	Hardwood Composite Fire Stile			
	Horizontal Edges*	Manufacturer's standard construction			
	Face & Core Assembly Adhesive	Type 1			
	Core Construction	Mineral Core			
	Lite Openings / Louvers	N/A			
	Distance from Lock & Lite Cutouts	N/A			
	Details	N/A			
	Machining	Machining preparation per hardware manufacturer's templates			
Factory Finish	Prime, standard and custom paint colors				
STC	Acoustic Rating	N/A			
CREDITS & STANDARDS	Environmental Options	- CARB PH2/TSCA Title VI Compliant - ULEF/NAUF* upon request			
	Environmental Product Declaration	Yes			
	Quality Standards	WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)			
	WDMA Performance Duty Level	N/A			
WT.	Door Weight	Thickness	lbs/sf		
		1-3/4"	5.5		
	Warranty	Limited Lifetime. No exterior warranty. Interior use only.			

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

* Fire-Rated doors will be constructed per label service listing and may deviate from above.

*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.