

# Standard Painted Doors

## CENDURA® SERIES

# Fire-Resistant Particleboard Core 45 Min / Bonded Construction Hardboard



	<b>Models</b>	C-PC-B-FR45			
<b>DIMENSIONS</b>	<b>Thickness</b>	1-3/4"			
	<b>Maximum Size</b>	ITS-WH and UL Sizes noted in this table are specific to 1-3/4" doors. Contact sales for information regarding other door thickness types.			
			Neutral Pressure	CAT A Positive Pressure	CAT B Positive Pressure
		Singles	4'0"x8'0"	4'0"x8'0"	4'0"x8'0"
		Pairs	6'0"x7'0"	6'0"x7'0"	6'0"x7'0"
DE Pairs	N/A	N/A	N/A		
<b>CONSTRUCTION</b>	<b>Surface Material</b>	Tempered Hardboard			
	<b>Crossbands</b>	N/A			
	<b>Vertical Edges*</b>	HDF Fire Stile			
	<b>Horizontal Edges*</b>	Manufacturer's standard construction per label service listing			
	<b>Face &amp; Core Assembly Adhesive</b>	Type 1			
	<b>Core Construction</b>	Fire-resistant wood based particleboard core			
	<b>Lite Openings / Louvers</b>	<ul style="list-style-type: none"> <li>- Factory glazing recommended-max 5/16" glass thickness</li> <li>- Standard metal vision frames</li> <li>- Standard fusible link door louver</li> </ul>			
	<b>Distance from Lock &amp; Lite Cutouts</b>	3-1/4" minimum distance from adjacent lock and lite cutouts			
	<b>Details</b>	Standard and custom applied moulding profiles			
	<b>Machining</b>	Machining preparation per hardware manufacturer's templates. Some limitations apply.			
	<b>Factory Finish</b>	Prime, standard and custom paint colors			
<b>STC</b>	<b>Acoustic Rating†</b>	N/A			
<b>CREDITS &amp; STANDARDS</b>	<b>Environmental Options</b>	<ul style="list-style-type: none"> <li>- CARB PH2/TSCA Title VI Compliant</li> <li>- FSC upon request</li> </ul>			
	<b>Environmental Product Declaration</b>	Yes			
	<b>Quality Standards</b>	WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)			
	<b>WDMA Performance Duty Level†</b>	Extra Heavy Duty			
<b>WT.</b>	<b>Door Weight</b>	Thickness	lbs/sf		
		1-3/4"	6.4		
	<b>Warranty</b>	Limited Lifetime. No exterior warranty. Interior use only.			

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

\* Fire-Rated doors will be constructed per label service listing and may deviate from above.

† Performance Duty Level and STC Ratings are based on 1-3/4" doors.

\*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.