

Standard Painted Doors

CENDURA® SERIES

Particleboard Core Non-Rated & 20 Min / Non-Bonded Construction Tempered Hardboard



	Models	C-PC-NB-NR C-PC-NB-FR20				
DIMENSIONS	Thickness	1-3/8", 1-3/4"				
	Maximum Size	ITS-WH and UL- Max 20 Minute Sizes noted in this table are specific to 1-3/4" doors. Contact sales for information regarding other door thickness types.				
			Non-Rated	Neutral Pressure	CAT A Positive Pressure	CAT B Positive Pressure
		Singles	4'0"x8'0"	3'0"x8'0"	3'0"x8'0"	3'0"x8'0"
		Pairs	8'0"x8'0"	6'0"x7'0"	N/A	6'0"x7'0"
DE Pairs	8'0"x8'0"	6'0"x7'0"	N/A	6'0"x7'0"		
CONSTRUCTION	Surface Material	Tempered Hardboard				
	Crossbands	N/A				
	Vertical Edges*	Default: Finger-Jointed Softwood (1-1/4" before trim) Alternate Stile Options Upon Request: N/A				
	Horizontal Edges	Default: Structural Composite Lumber (1-1/4" before trim) Alternate Rail Options Upon Request: - Wide rails allowed on 1-3/4" thick doors only				
	Face & Core Assembly Adhesive	Type 1				
	Core Construction	Wood-based particleboard core				
	Lite Openings / Louvers	- Factory glazing recommended-max 5/16" glass - Available with standard profile wood beads and standard metal vision frames - Standard wood louvers-non-rated doors only				
	Distance from Lock & Lite Cutouts	3-1/4" minimum distance from adjacent lock and lite cutouts				
	Details	Standard and custom profiles of applied mouldings				
	Machining	Machining preparation per hardware manufacturer's templates				
Factory Finish	Prime, standard and custom paint colors					
STC	Acoustic Rating	N/A				
CREDITS & STANDARDS	Environmental Options	- CARB PH2/TSCA Title VI Compliant				
	Environmental Product Declaration	Yes				
	Quality Standards	WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)				
	WDMA Performance Duty Level	N/A				
WT.	Door Weight	Thickness	lbs/sf	Thickness	lbs/sf	
		1-3/8"	4.2	1-3/4"	5.3	
	Warranty	Limited Lifetime. No exterior warranty. Interior use only.				

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

* Fire-Rated doors will be constructed per label service listing and may deviate from above.

*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.