

Standard Painted Doors

CENDURA® SERIES Hollow Core Molded Panel



	Models	C-HC-NB-MP-NR			
DIMENSIONS	Thickness	1-3/8", 1-3/4"			
	Maximum Size	3'0"x7'0" Standard-all Designs 3'0"x8'0" 2-Panel 3'6"x7'0" 6-Panel (3'6" width is only available in the 6-Panel Commercial Smooth design) Bifolds Available			
CONSTRUCTION	Surface Material	Molded Panel			
	Crossbands	N/A			
	Vertical Edges	Default: FJ Softwood (1-1/4" before trim)			
	Horizontal Edges	Default: Softwood (2-1/2" before trim)			
	Face & Core Assembly Adhesive	Type 1			
	Core Construction	5-1/2" Kraft Paper Honeycomb. Lock Blocks (2) per door. 3" x 20" for 1-3/4", 3" x 16" for 1-3/8"			
	Lite Openings / Louvers	No lites/No louvers			
	Distance from Lock & Lite Cutouts	N/A			
	Details	N/A			
	Machining	Machining preparation per hardware manufacturer's templates			
	Factory Finish	Primed, standard and custom paint colors			
STC	Acoustic Rating	N/A			
CREDITS & STANDARDS	Environmental Options	- CARB PH2/TSCA Title VI Compliant - ULEF/NAUF* upon request			
	Environmental Product Declaration	Yes			
	Quality Standards	WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)			
	WDMA Performance Duty Level	N/A			
WT.	Door Weight	Thickness	lbs/sf	Thickness	lbs/sf
		1-3/8"	1.3	1-3/4"	1.7
	Warranty	One Year. No exterior warranty. Interior use only.			

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.