

ECONOMY SERIES - WOOD VENEER DOORS

HOLLOW CORE

NON-RATED

	PRODUCT SPECIFICATIONS	INTERIOR USE ONLY	
DIMENSIONS	Thickness	1-3/8", 1-3/4"	
	Maximum Size		Non-Rated
		Singles	3'0" x 8'0"
		Bifolds	6'0" x 7'0" (4-door)
	Prefit Size (Default)	1-3/4" Thick Doors: Beveled 2 edges, 7/32" width and full height 1-3/8" Thick Doors: Square edges, full size	
CONSTRUCTION	Surface Material	Wood Veneers: Thin Face and Select Grade, book and running match Species: Rotary Natural Birch and Plain Sliced Red Oak	
	Crossbands	One Piece Medium Density Fiberboard (MDF)	
	Vertical Edges	Mill Option: Full Length Softwood Stiles (1-1/4" before trim) Red Oak veneer edge band applied to 1-3/4" thick Red Oak doors	
	Horizontal Edges	Mill Option: Softwood Rails (2-1/2" before trim)	
	Face & Core Assembly Adhesive	Type 2	
	Core Construction	5-1/2" Kraft Paper Honeycomb Lock blocks (2) per door	
	Lite Openings / Louvers	No Lites / No Louvers	
	Distance from Lock & Lite Cutouts	N/A	
	Details	N/A	
	Machining	Machining preparation per hardware manufacturer's templates; some limitations apply	
	Factory Finish	- Clear - Standard and custom stain colors not recommended; limited availability	
CREDITS & STANDARDS	Environmental Standards	CARB PH2 / TSCA Title VI Compliant	
	Quality Standards	Manufacturer's internal quality standards	
	WDMA Performance Duty Level	N/A	
WT.	Door Weight	Average: 1.7 lbs/sf	
	Warranty	Limited One Year. No exterior warranty. Interior use only.	