

PRODUCT SPECIFICATIONS

Fiber Content	100% EnVisionSD® BCF Nylon
Dye Method	Solution Dyed
Construction	Loop
Pattern Repeat	1" W x 1" L
Gauge	1/12
Pile Height	.155"/.275"/.350/.458"
Tufted Fiber Weight	32 oz.
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene

PERFORMANCE

Flammability	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness	4.0 or better.
Static Rating	Less than 3.5 kV.

WARRANTY

- 10 year commercial warranty.

COLOR LINE

00136	Volts	00237	Electrode	00335	Ionic	00638	Waves
00640	Delta	00641	Daydream	00730	Impluse	00734	Neuron
00831	Grey Matter	00832	Rhythm	00833	Pulse	00939	Theta

Alpha meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678.

