

## **INSTALLATION INSTRUCTIONS**

# 2007-2013 TOYOTA TUNDRA REAR BUMPER PART #TN-2961



#### **Hardware list:**

	M12X1.75X40mm
10	M12X1.75 nut
30	M12 Washer



## **INSTALLATION INSTRUCTIONS**

#### **Removing Factory bumper:**

- 1. Remove plastic center section from top of rear bumper, and from under license plate.
- 2. Disconnect license plate light. Remove factory light and retain for later use.
- 3. Remove bolts securing bumper skin to frame and receiver brackets. Retain hardware for later use.
- 4. Remove bumper skin at this time.

#### **Bumper Installation For Tn-2961:**

We recommend you have help with lifting of the rear bumper to avoid injury or damage to bumper and vehicle.

1. Remove 2 right side bolts securing bumper and or receiver mount to frame only.






- 2. Install right side bracket with factory bolts and M12X1.75X40mm bolts and hardware. Leave loose at this time.
- 3. Repeat above step on left side.



## **INSTALLATION INSTRUCTIONS**

4. Using M12x1.75x40mm bolts, washers and nuts attach TN-2961 with D-ring plates to bumper brackets.



- 5. Align bumper to body and tighten all hardware at this time
- 6. Check for clearance when tailgate is open. Reinstall factory license plate lights.
- 7. Install d-rings.