OWNERS MANUAL

CARE AND MAINTENANCE

Congratulations on your Safariland purchase. You have selected a product with construction technology that is unique and state of the art in the manufacturing of holsters, belts, and accessories.

The product you have received is constructed with a proprietary SafariSeven material. Care and maintenance of this product are dictated by the material from which it is constructed. Use of an incorrect cleaning material may result in damage to the finish of the product.

SafariSeven can be cleaned by wiping with a damp cloth. Any liquid or powder soap and water along with a scouring pad will assist in cleaning.

It is important to note that most natural man-made products may eventually wear out or become unsuitable for the function for which they were designed. Stress and strain placed on any given holster vary according to usage; therefore it is difficult to indicate a recommended replacement date. It is the users responsibility to assure after use, that the holster is able to continue service within its design parameters.

It is the users responsibility to inspect products daily for signs of excessive wear or loss of retention of the handgun, and tightness of all screws and hardware. If any possible problem is detected or any doubt exists, do not use. Contact the Safariland Customer Care at (800) 347-1200.

Read and understand all owners manuals, instructions, and guides prepared by the manufacturer your handoun.

OWNERS MANUAL

WARRANTY

EXPRESS LIMITED WARRANTY FOR HOLSTER AND ACCESSORY PRODUCTS

Safariland (the Company) warrants its holster products to be free from defects in materials and workmanship for a period of two (2) years from date of purchase. This warranty is subject to the proper Care and Maintenance of the product and proper use of the product as detailed in the Consumer and Safety Information.

If you believe this product has any defects in materials or workmanship, cease use immediately and contact customer service for a remedy. If a product proves to be defective in material or workmanship, we will repair or replace the product and send it to you at the Companys expense. All returns must include the proof of purchase and documentation specifying the adjust the claimed defect.

This is a LIMITED WARRANTY, and is the sole and exclusive warranty of this product by the Company. It shall not be enlarged by any representations, descriptions, course of dealing, trade usage, rendering of technical advice, service or otherwise. Furthermore, it shall not be altered or expanded by any acts, statements, or agreements of any dealer, employee or agent of the Company (other than by a duly authorized officer of the Company).

THE COMPANY MAKES NO OTHER WARRANTIES EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

IN NO EVENT SHALL THE COMPANY BE LIABLE FOR ANY PUNITIVE, EXEMPLARY, OR CONSEQUENTIAL DAMAGES, ANTICIPATED OR LOST PROFITS, INCIDENTAL DAMAGES, LOSS OF TIME, OR OTHER INDIRECT LOSSES OR EXPENSES THAT ARISE FROM ANY CAUSE RELATING TO THE PRODUCT, REGARDLESS OF THE FORM OF THE ACTION, WHETHER IN TORT (INCLUDING NEGLIGENCE), CONTRACT, STRICT LIABILITY OR OTHERWISE, AND REGARDLESS OF WHETHER THE COMPANY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

For any warranty issue, please contact customer care for a prompt resolution to your concern at the number provided below.



3041 Fave Road Jacksonville, Florida 32226 Customer Care: 800-347-1200 (USA Only) or 909-923-7300

©2017-2019 Safariland, LLC (03/19)

OWNERS MANUAL SAFARILAND[®] USERS GUIDE

MODELS 7360 & 7365



READ AND UNDERSTAND ENTIRE MANUAL BEFORE USING HOLSTER

U/G-00000WHA-201 1315699

holster, doing so without a weapon could result in damage to the holster. increase tension by turning clockwise while unloaded weapon is in the clockwise to increase tightness, and counterclockwise to reduce. Only below, use included Allen wrench, insert fully into tension device cavity, turn customization for the user. To adjust this tension device as seen in photo of tolerance for weapon variances as well as provide a level of triction adjustment mechanism. This mechanism is designed to give a wider range CRUTION: To draw Certain 7TS models may have an underside tension . volster.

Be certain the SLS hood is clear of handgun prior to drawing out of encountered until handgun is released from holster seat. CAUTUAS: and draw straight up out of holster. A bit of resistance should be and hammer. The first and second operation can become one motion with practice and proper technique. Third, use the thumb to move ALS®ejection port locking lever far back enough for handgun to clear and draw straight up out of holster. A bit of resistance should be Second, use thumb to rotate SLS hood forward and clear of handgun straight, with the thumb press the thumb tab down to release lock. First, while obtaining a shooting grip with the trigger finger extended To draw the handgun, it is necessary to use a three-step process. 7 d3LS

natural.

holstering and securing of thumb tab/hammer strap is smooth and after practice. Steps 2 and 3 should be practiced until a one-handed up in the locked position. This action should become very natural rearward over hammer or back of slide until the SLS unit clicks

engaged when holstering the handgun.

If your handgun is equipped with a safety lever, be sure that safety is

accidental discharge) of carrying a loaded handgun. holster and are willing to assume responsibility and risk (including have received professional training in the use of the handgun and no vor carry any handgun with a round in the chamber unless you

holster for proper fit with the handgun in an unloaded condition Do not place a loaded handgun in a holster without first testing the

'əsn pue

ot and be properly trained in all aspects of tirearm and holster safety injury or death. It is the users responsibility to have thorough knowledge Improper or careless use of a firearm and holster may result in serious

experience with holsters and handguns of each particular user. training required will depend upon the dexterity, coordination and prior continued as long as it is to be used. The amount of practice and Regular practice to assure proficiency is using the holster must be

.92U 9163

an unloaded handgun until thoroughly competent and proticient in its handgun during practice and training. Practice using the holster with mandatory prior to using the holster on duty. Do not use a loaded CRUTION: Practice and training as prescribed in this manual are

exclusive risk of the user.

The purchase and use of this Safariland holster is done at the sole and

handgun in an ill-fitting or improper holster can result in serious injury

Safariland Customer Care department at (800) 347-1200. Carrying a

handgun. If there is any doubt, do not use the holster. Contact the

Safariland holsters are designed to carry specific handguns. Before

result in accidental discharge of a handgun causing serious injury or

Failure to heed these warnings or follow the operating instructions may

remove product from heat. Allow product to cool to room temperature

place. If accidental high heat exposure has occurred immediately

to high heat in some cases can cause the handgun to be locked into

of 200 F, even several feet away from certain heating source. Exposure

efficiently absorb radiant hear and can reach temperatures in excess

manufactured. The non-reflective surface on Safariland products will or destroy the polymer from which many Safariland products are

a heat source. Space heaters, radiators, heating registers, fireplaces,

WARNING! Never store your Safariland holster or accessories near

or other heating sources emit high temperatures that can deform

use, be sure holster selected is designed to carry corresponding

and operate to ensure correct function.

. death.

JOIUD SATAU® USERS GUIDE OWNERS MANUAL

J360

OPERATING INSTRUCTIONS WODEF 7360 & 7365

1 dats

.tl9d holster, it is necessary to install on a 2.25 (58 mm) or 2 (50 mm) duty In order to draw a handgun from a Safariland Model 7360 or 7365

392

STEP 2

is thoroughly seated in holster with ejection port lock engaged. place thumb over the hammer or behind the slide. Be certain handgun front of the trigger guard. When inserting handgun in holster, always adjacent but away from the trigger and if possible support tip of on the place finger in trigger guard or near the trigger. Position trigger finger handgun straight down. When placing handgun in the holster do not the tab down rotate the SLS hood forward and insert the unloaded To insert handgun push down on thumb tab area and while holding

STEP 3

After handgun is properly seated in holster, rotate the SLS hood

GOOH DNITATOR SJS

the weapon useless before the SLS rotating hood is affected. operate the SLS rotating hood. Those same conditions usually render as mud, dry sand, and airborne grit will cause additional force to extremely dirty conditions. Testing has shown that conditions such device and could require cleaning and lubrication if exposed to Like the weapon it encloses, the SLS mechanism is a mechanical ports in order to function under extreme environmental conditions. resistant plastic. It is designed with extra tolerances and clearing The SLS mechanism is composed of stainless steel and chemically

every time you inspect, clean and lubricate your handgun. a practical matter inspect, clean and lubricate the SLS mechanism the hood until the unit works smoothly, then lubricate with gun oil. As a similar aerosol product using the plastic straw nozzle while rotating been exposed to dry sand or frit, it should be cleaned with WD-40 or sen meinedown SLS and gun oil. If the SLS mechanism has flush with warm water while rotating the hood until the unit works SLS mechanism has been exposed to mud and the unit is still wet, instructions and then clean the SLS rotating hood system. If the as soon as practicable clean the handgun per the manufacturer If the holster and weapon have been exposed to such conditions

SDNINRAW & SNOITUAD

a surprise command to completed draw. under simulated stress or life-threatening situation. Have a partner time a draw from a fully secured holster in less than two seconds while CAUTION: Prior to wearing the holster on duty, the user must accomplish

Customer Care department at (800) 347-1200. bind or remain tight, cease use immediately and contact the Safariland silicone spray to the inside of the holster. Should the holster continue to remain tight after a reasonable beak-in period, apply a liberal amount of drawing standard indicated above is accomplished. Should the holster be used with a loaded handgun or on duty until the under two-second easonable break-in period has occurred. Thus, the holster should not A handgungated in a new holster will fit more tightly than after a

support the tip of the finger on the front of the trigger guard. trigger finger adjacent to but away from the trigger and, if possible, not place finger in the trigger guard or near the trigger guard. Position When drawing a handgun from a holster or placing it into a holster, do

hammer or behind the slide. When putting a handgun in the holster always place thumb over the

strap or any other object to enter the trigger guard. trigger guard when putting the handgun in the holster. Do not allow Always keep hammer strap and thumb break forward or clear of

'aptalod ni nubbned Always secure the retaining or safety strap(s) on holster after inserting

Browning Hi-Power). (except handguns which are single action only; ex. Colt 1911 or the Never holster any semi-automatic handgun in a single-action mode

accidental discharge. damage to the handgun or holster or both and may contribute to an Do not attempt to cock a holstered handgun as this can cause severe

performing other vigorous activity. Always place hand on the handgun and holster when running or

.s191810n that are not of original manufacturers specifications in Safariland Do not use customized, modified, worn or broken handguns or those

holster. Do not, in any way modify, disassemble or remove any part from this

Do not expose this holster to extreme heat conditions.

Do not leave holster in trunk of vehicle during extremely hot weather.

holster. Rely only on extensive, proper training and vigilance. Do not rely on any holster being snatch proof. There is no such

checking components such as snaps, screws, etc for proper function. It is the users responsibility to properly maintain the holster by

αθόμι στι το προτατικά το ποια ματά το ποια το παραγιατικό το παραγιατικό το παραγιατικό το παραγιατικό ποι παρ Be aware that handguns with lights mounted to them create an