



GBC DIRT COMMANDER - ATV/UTV Tires

SIZE	PLY RATING	TREAD DEPTH 32ND IN.	OVERALL DIAMETER	SECTION WIDTH	RIM WIDTH	WEIGHT LBS.	PSI	MAX LOAD
25X8.00-12	8PR	27	25.2	8.2	5-7	20.5	7/12	340/480
25X10.00-12	8PR	27	25.2	9.5	6-8	25.9	7/12	420/580
26X9.00-12	8PR	27	25.7	8.75	6-7	23.7	7/12	410/570
26X11.00-12	8PR	27	25.8	10	7-9	27.1	7/12	480/680
27X9.00-12	8PR	26	27.7	8.5	6-7	25	20	750/920
27X11.00-12	8PR	26	27.8	10.6	7-9	29.3	20	780/960
28X10.00-12	8PR	27	27.9	9.6	6-8	29.3	20	855
26X9.00-14	8PR	27	26	8.5	6-7	23.4	7/14	700/1000
26X11.00-14	8PR	27	26	9.7	7-9	28.2	7/14	730/1045
27X9.00-14	8PR	27	27	8.5	6-7	24.6	20	750/1075
27X11.00-14	8PR	27	27	10	7-9	29.4	20	780/1120
29X9.00-14	8PR	26	29.5	8.5	5-7	28.2	20	925
29X11.00-14	8PR	26	29.6	10.4	7-8	33	20	985
30X10.00-14	8PR	26	30.6	9.8	6-8	33.7	20	1050
32X10.00-14	8PR	27	32	9.6	6-8	36.2	20	1070
30X10.00-15	8PR	26	30.8	9.5	6-8	38	20	890

*True specifications achieved after mounting for 24-72 hours