

Modular carpet tiles


Product Specifications

Style Name	Calando
Style Number	40095
Product Type	Tile
Surface Texture	Multilevel Loop
Pile Fibre Content	100% BCF Anti-Static Colorloc nylon
Dye System	Solution Dyed
Primary Backing	Non-Woven Polyester
Secondary Backing	Fiberglass Reinforced Thermoplastic


	<u>Imperial</u>	<u>Metric</u>
Pile Weight	20.0 oz / s.y.	678 g/m ²
Gauge	1/12 ga	47.2 / 10 cm
Stitches	9.5 / in.	37.5 / 10 cm
Pile Height	0.140 in.	3.5 mm
Pile Thickness	0.118 in.	3.0 mm
Density Factor	6102	10.3 ktex
Total Weight	108.41 oz / s.y.	3675 g/m ²
Width	19.68" x 19.68"	50 cm x 50 cm

Performance Specifications


Flammability	Meets ASTM E-648 test standards Radiant Panel Class I
Smoke Density	Meets ASTM E-662 test standards <450 Flaming mode
Anti-Static Properties	Less than 3.0 kv at 20% R.H.. & 21° C
Dimensional Stability	Less than 0.05 %
Lightfastness	L5 or Better
Resistance to Wet Cleaning	Grey Scale 5
Installation Method's	Quarter-Turn, Ashlar, Brick



Quarter Turn



Brick



Ashlar

Warranty Information

- 15-years Commercial Wear & Anti-Static
- 25-years Residential Wear & Anti-Static
- Limited Lifetime Against Delamination
- Limited Lifetime on Dimensional Stability
- Limited Lifetime Against Backing Deterioration

Environmental

Indoor air quality no.	GLP 3315
------------------------	----------