



GBC MONGREL ATV/UTV Tires

SIZE	PLY RATING	TREAD DEPTH 32ND IN.	OVERALL DIAMETER	SECTION WIDTH	RIM WIDTH	WEIGHT LBS.	PSI	MAX LOAD
23X10.00R12	6PR	13	23.39	9.6	6-8	22.5	20	615
25X8.00R12	10PR	20	25.28	8.1	5-7	23.7	20	600
25x10.00R12	10PR	20	25.39	9.4	6-8	27	20	715
26x10.00R12	10PR	20.9	26.4	9.1	6-8	28.5	20	760
27X9.00R12	10PR	19.9	27.3	8.9	6-7	28.7	20	760
27X11.00R12	10PR	20.1	27.4	10.2	7-9	31.4	20	855
27X9.00R14	10PR	19.9	27.4	8.7	6-7	28	20	715
27X11.00R14	10PR	19.5	27.6	9.7	7-9	30.8	20	855
28x10.00R14	10PR	19.5	28.5	9.1	6-8	31	20	855
30x10.00R14	10PR	19.5	30.6	9.4	6-8	36.8	20	935
32x10.00R14	10PR	19.5	32.5	10.1	6-8	40.7	20	1070
28x10.00R15	10PR	19.9	28.7	9.3	6-8	29.6	20	825
30x10.00R15	10PR	19.1	30.7	9	6-8	37.8	20	910
32x10.00R15	10PR	19.1	32.4	9.6	6-8	41.4	20	1050
33x10.00R15	10PR	19	33.3	9.7	6-8	48	20	1140
35x10.00R15	10PR	19	35.2	10.2	6-8	52.9	20	1235

*True specifications achieved after mounting for 24-72 hours