



## GBC DIRT DEVIL - ATV/UTV Tires

SIZE	PLY RATING	TREAD DEPTH 32ND IN.	OVERALL DIAMETER	SECTION WIDTH	RIM WIDTH	WEIGHT LBS.	PSI	MAX LOAD
22X11.00-8	6PR	20	22.3	10.9	7-9	21.5	7	395
22X11.00-9	6PR	20	22.5	10.8	9-Jul	21.6	7	395
25X12.00-9	6PR	20	25.2	11.6	8-10	23.9	7	496
22X11.00-10	6PR	20	22.2	10.7	7-9	19.9	7	385
23X10.00-10	6PR	20	23.4	10.2	6-8	19.8	7	375
22X8.00-10	6PR	20	21.9	8	5-7	14.2	7	275
23X8.00-10	6PR	20	23.4	8.3	5-7	15.4	7	300
24X11.00-10	6PR	20	24	11.1	7-9	22.3	7	440
25X12.00-10	6PR	20	24.8	11.7	8-10	24.9	7	495
24X9.00-11	6PR	20	23.8	8.6	6-7	19.1	7	365
24X8.00-11	6PR	20	24	8.1	5-7	17.4	7	320
23X8.00-11	6PR	20	23.4	7.6	5-7	14.5	7	290
24X10.00-11	6PR	20	24.2	10.1	6-8	21.4	7	395
25X10.00-11	6PR	20	25.2	10	6-8	23.1	7	430
25X8.00-12	6PR	20	25.2	8.3	5-7	19.3	7	340
25X10.00-12	6PR	20	24.4	9.9	6-8	20.2	7	420
26X10.00-12	6PR	39	25.9	9	6-8	24.4	7	460
27X12.00-12	6PR	39	26.9	11.4	8-10	32	7	550

\*True specifications achieved after mounting for 24-72 hours