



SEMI TRUCK STAIRS

THE PERFECT LIGHT-WEIGHT HEAVY-DUTY SOLUTION

NON-SLIP
SURFACE

RELOCATABLE

INDUSTRIAL
ALUMINUM



COMPLIANT TRAILER STEPS

The Occupational Safety and Health Administration (OSHA) sets forth standards for all aspects of working conditions to ensure that all employees have a safe working environment. Upside's Trailer Steps comply with the current OSHA guidelines while providing safe travel in and out of a semi trailer.

ALWAYS INSIST ON ALUMINUM

Our all-aluminum products will never rust which means they are a low-maintenance product and have a long life cycle. Aluminum should be your preferred material over steel, wood, and plastic. More and more, aluminum is replacing plastic and steel components, as it is stronger and tougher than plastic and lighter than steel.

NON-SLIP

Our steps use an aggressive open diamond serrated tread for maximum foot traction even in snowy conditions.

OPTIMAL WIDTH

4' wide to allow two-way traffic.

STRENGTH-TO-WEIGHT RATIO

Lightweight yet high tensile strength.

STANDARD HEIGHTS

The standard Upside Trailer Steps are 40" high, so the last 8 inches step up into the 48" trailer.

**SINGLE TOP STEP****DOUBLE TOP STEP****48" X 57" PLATFORM**

AGGRESSIVE TREAD

Heavy duty 3" open diamond serrated tread

OPTIMAL WIDTH


4' wide to allow two-way traffic

SAFE DESIGN

Step rails on both sides of the step for increased stability

NON-SLIP AGGRESSIVE OPEN DIAMOND SERRATED TREAD

Keeping your workers safe from slips and falls in any weather condition.



OPTIMAL STRENGTH-TO-WEIGHT RATIO

Lightweight yet high tensile strength

RELOCATABLE

Only weighs 72-86 lbs. so that it can be lifted into the trailer

OPTIONAL CASTERS

Optional Casters to help easily move the semi trailer steps around your job site