

Ultra-Containment Berm®

Modular Model (Gorilla Berm™)



Versatile spill containment that can be reused and easily modified

KEY FEATURES AND BENEFITS

- Modular construction allows containment areas of any size to be configured.
- Polymer-coated foam support blocks (6' lengths) provide structure to sidewalls - can be driven over repeatedly without damage.
- Standard materials include 38 mil and 54 mil slip resistant PVC. Other materials available upon request.

SIDEWALLS

- Triangular-shaped, polymer-coated foam support blocks (72"L x 16"W x 6"H) are used with rebar (not included) to provide sidewall structure.
- Separate 90-degree corner support blocks provide complete support and security where sidewalls meet.
- Molded-in slots in top of foam blocks hold rebar - secures material in place.
- No set-up required once Berm has been positioned in the field.

COMPLIANCE

- EPA 40 CFR 264.175 Containment of Containers Containing Free Liquid.
- SPCC - Spill Prevention, Control and Countermeasure Act



Part#	Description/Dimensions ft. (m) Wall Height: 6 in. (152 mm)	Containment Capacity gal (L)	Weight lbs. (kg)
8740	7 x 13 (2.1 x 4.0)	366 (1,385)	165.0 (74.5)
8741	13 x 13 (4.0 x 4.0)	665 (2,517)	220.0 (100.0)
8742	13 x 25 (4.0 x 7.6)	1,263 (4,781)	332.0 (150.5)
8743	13 x 31 (4.0 x 9.4)	1,563 (5,917)	387.0 (176.0)
8744	13 x 34 (4.0 x 13.1)	2,161 (8,180)	491.0 (222.5)
8745	13 x 55 (4.0 x 16.8)	2,759 (10,444)	610.0 (278.0)
8746	13 x 61 (4.0 x 18.6)	3,059 (11,580)	666.0 (302.0)
8747	25 x 55 (7.6 x 16.8)	5,243 (19,847)	868.0 (393.5)
8748	31 x 55 (9.4 x 16.8)	6,485 (24,548)	1,004.0 (455.5)
8749	55 x 55 (16.8 x 16.8)	11,452 (43,351)	1,502.0 (681.5)
8730	Support Block Only	NA	11.0 (5.0)
8731	Corner Support Block Only	NA	6 (2.7)



Ultra-Grip

SPECIFICATIONS

Ultra-Grip is used with UltraTech's line of spill containment berms. This 22-oz. material is an unbalanced, high-grip, anti-skid coated vinyl fabric with a diamond emboss that is ideal for industrial, oilfield and construction applications.

	English	Metric	Testing Method
Weight	22 oz./yd ²	746 g/m ²	FS 5040 / ASTM D3776
Widths	up to 126"	up to 320 cm	
Construction	20 x 10/1" by 1000 x 2000	8 x 4/cm by 1100 x 2200	
Grab Tensile	559 x 592 lbs./2"	2488 x 2633 N/5 cm	FS 5100 / ASTM D5034
Tongue Tear	121 x 136 lbs./2"	538 x 605 N/5 cm	FS 5134 / ASTM D2261
Adhesion	24 lbs./2"	108 N/5 cm	FS 5970 / ASTM D751
Finish	Diamond		
Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Treatments	Anti-Mildew, UV		
Fire Retardant	California Tech. Bulletin 117 Sec. E, FMVSS-302		Pass

Ultra-Grip material has an excellent rating up to 20% HCL with no effect at 120F constant temperatures.