







DIMENSIONS:

WALK SURFACE WIDTHS (DIM A)	24"	36"	48"	60"	72"
CORRESPONDING OVERALL WIDTHS (DIM B)	42"	54"	66"	78"	90"

MODEL #	DIM C	DIM D	DIM E	DIM F	DIM G
3 STEP	48"	28"	65"	17"	15"
4 STEP	61"	29"	78"	26"	24"
5 STEP	74"	30"	91"	35"	32"
6 STEP	87"	31"	104"	44"	40"
7 STEP	100"	32"	117"	53"	49"

SAS SELF-ADJUSTING STAIR GANGWAY-G4

SPECIFICATIONS:

- TOTAL LOAD CAPACITY - 500 lbs., HANDRAIL-200 lbs., MID-RAIL-100 lbs.
- AVAILABLE WORKING RANGE - 45° ABOVE TO 40° BELOW HORIZONTAL.
- 2.9" DIAMETER HANDRAIL WITH 1" DIAMETER GRAB BAR.
- BASE TREAD HOT DIPPED GALVANIZED PER ASTM A 123.
- GANGWAY BODY CONSTRUCTED OF ALUMINUM (STAINLESS STEEL-OPTIONAL).
- SELF SUPPORTING BY USE OF ADJUSTABLE CHAIN STOPS.
- SPRING COUNTERBALANCED FOR EASE OF OPERATION.
- LOAD BEARING PIVOT POINTS CONTAIN OIL IMPREGNATED BRONZE BEARINGS.
- AWS WELDING SPEC. D 1.1-D 1.2.
- ALL CRITICAL HARDWARE IS STAINLESS STEEL.

