



CIVAICON MODEL 8030 GROUND VERIFICATION MONITOR

120/240 VAC
OPTIONS

CLEAR
MONITOR
INDICATORS

EASY TO
INSTALL
AND USE



Civacon Model 8030 Ground Verification Monitor from OPW-ES

The Model 8030 has been designed to allow the rack operator to visually confirm when a ground connection between the transport and the loading terminal has been achieved, resulting in increased safety and operational peace-of-mind while confirming rackequipment integrity when a trailer won't load.

Specifications

Product #: 8030-120 (120V) · 8030-240 (240V)
Operating Temperature: -40°F to 140°F (-40°C to 60°C)
Input Requirements: 120VAC 60 Hz, 10 VA (Standard) – 240VAC version available — please inquire
Output Relay Contacts: 240VAC — 5A
Electrical Connections: Internal terminal strips
Enclosures: NEMA 4 explosion-proof aluminum housing
Approximate Weight: 8030 — 13 lbs (6 kg)
Approvals: UL/CUL Class I, Division I, Groups C & D
Installation Information: Provided with the monitor. Can also be accessed and downloaded via website.

Features

- Compatible with most loading terminal ground schemes
- Easy to install and use
- Chassis is contained in a small explosion-proof enclosure
- Automatically operates via connections to the transport
- Lightweight: 13 lbs (6 kg)
- LED lamps for long life and reliability
- 100,000-hour minimum