

Films PRO PAK'R Renew 200x130

- Contains 50% recycled content
- 100% recyclable
- Void fill

These AirSpeed Renew air bags allow to void fill and block & brace products for optimal protection.

The film is created out of 50% recycled content. Post-consumer recycled content, to be precise. We strive for a circular economy and this recycled content embodies this. It is made from products that have been used by consumers and have been recycled after serving their purpose. In other words: it is sustainable and circular... the print included! This is printed on each air cushion with a water-based ink, so it's not harmful to the environment.

The film complies perfectly with the European legislation for packaging and packaging waste: EN13427.

Machine & Accessories

The PRO PAK'R is equipped with the latest technology. It is fast, smart, easy to use and compact. It works with various films.



Air Cushion Specifications

- Size cushion: WxL= 200x130 mm
- Thickness: 19 micron
- Material: LDPE
- Grey cushion, white print
- 100% recyclable
- Contains 50% recycled content
- Product code: 4079604



Pregis Europe

www.PregisEU.com

📞 00800 8888 8840 | 🔀 customer.care@pregis.com

Specifications

ROLLS

- Roll length: 1100 m
- Roll weight incl. core: 7.8 kg
- Core weight: 0.5 kg
- Volume per roll: 7.5 m³
-

PALLET

- Rolls per pallet: 66
- Number of layers:
- Rolls per layer:
- Pallet weight:
- Pallet dimensions:
- 540 kg LxWxH in cm=

6

11

120x80x140

Packing Applications







Block & Brace



Characteristics

Environmental Friendly

- Made of 50% recycled content
- 100% recyclable
- Very light, 99% air
- Complies with EN13427 standard for packaging and packaging waste
- Printing is made from water-based ink print

Technical Specifications

- Non-toxic
- Groundwater neutral
- Chemically inert
- Dust-free
- Problem-free transport via existing PE recycling systems
- Water repellent

Storage Conditions

- Store covered in a clean dry room
- Average storage condition should be 20°C (max. 30°C)
- During winter we recommend to store the rolls on site at room temperature at least 24 hours before use
- Keep the rolls out of direct sunlight
- Rolls must be kept at least 2m from any heat source



Pregis Europe

www.PregisEU.com

📞 00800 8888 8840 | 🔀 customer.care@pregis.com