



Films PRO PAK'R Double Cushion LD

- Air-transfer technology
- 100% recyclable
- RFID technology

These air bags allow to fill large voids while remaining flexible. Thanks to the air transfer technology, the air cushion is able to absorb shocks, providing a high protection of packages.

Reusable and 100% recyclable, the ink on the air cushions is water based and not harmful to the environment.

The film complies perfectly with the European legislation for packaging and packaging waste: EN13427.



Machine & Accessories

The PRO PAK'R is equipped with the latest technology. It is fast, smart, easy to use and compact. It works with various films.



Air Cushion Specifications

- Size cushion: WxL = 460x152 mm
- Thickness: 23 micron
- Material: LDPE
- Green print, cushion clear & transparent
- 100% recyclable
- Product code: 4078986

Pregis Europe

www.PregisEU.com

☎ 00800 8888 8840 | ✉ customer.care@pregis.com



Specifications

ROLLS

- Roll length: 457 metre
- Roll weight: 8 kg
- Volume per roll: 10.5 -11.0 m³

PALLET

- Rolls per pallet: 42
- Number of layers: 2
- Rolls per layer: 21
- Pallet weight: 490 kg
- Pallet dimensions: LxWxH in cm= 120x80x109



Characteristics

Environmental Friendly

- 100% Recyclable
- Suitable for energy recovery
- Very light, 99% air
- Complies with EN13427 standard for packaging and packaging waste
- Printing is made from water-based ink

Technical Specifications

- Non toxic
- Groundwater neutral
- Chemically inert
- Dust-free
- Wear-resistant
- Can be transported problem free via the existing recycling systems for PE
- Water repellent

Storage Conditions

- Store covered in a clean dry room
- Average storage condition should be 20°C (max. 30°C)
- During winter we recommend to store the rolls on site at room temperature at least 24 hours before use
- Keep the rolls out of direct sunlight
- Rolls must be kept at least 2m from any heat source

Applications



- Void Fill



- Block & Brace

Pregis Europe

www.PregisEU.com

☎ 00800 8888 8840 | ✉ customer.care@pregis.com