



Films PRO PAK'R Double Cushion LD

- Air-transfer technology
- RFID technology
- Flexible void fill

An air cushion that combines a high volume yield with air-transfer technology: high-quality protection at a low cost.

The Double Cushion fits perfectly with a large range of cardboard boxes.

100% recyclable, the ink on the air cushions is water based, therefore not harmful to the environment. The film connects perfectly with the European legislation for packaging and packaging waste: EN13427.



Machine & Accessories

The PRO PAK'R is equipped with the latest technology. It is fast, smart, easy to use and compact. It works with various films.



Air Cushion Specifications

- Size cushion: WxL= 386x152 mm
- Thickness: 35 micron
- Material: LDPE
- Green print, cushion clear & transparent
- 100% recyclable
- Product code: 4078993

Pregis

The Netherlands
Nijverheidsweg 4,
6422PD Heerlen

United Kingdom
Gunnels Wood Road,
Stevenage, Herts, SG1 2DG

France
9 Bis Avenue Louis de Broglie,
ZI Vert Galant, BP67016
Saint-Ouen l'Aumône, 95050
Cergy Pontoise Cedex

Germany
Nelmannswall 4,
59494 Soest

☎ 00800 8888 8840 | ✉ customer.care@pregis.com

www.pregis.com

Specifications

ROLLS

- Roll length: 457 metre
- Roll weight: 11.5 kg
- Volume per roll: 8.0 - 8.5 m³

PALLET

- Rolls per pallet: 45
- Number of layers: 3
- Rolls per layer: 15
- Pallet weight: 564 kg
- Pallet dimensions: LxWxH in cm= 120x80x133



Characteristics

Environmental Friendly

- 100% Recyclable
- Suitable for energy recovery
- Very light, 99% air
- Complies with EN13427 standard for packaging and packaging waste
- Printing is made from water-based ink

Technical Specifications

- Non toxic
- Groundwater neutral
- Chemically inert
- Dust-free
- Wear-resistant
- Can be transported problem free via the existing recycling systems for PE
- Water repellent

Storage Conditions

- Store covered in a clean dry room
- Average storage condition should be 20°C (max. 30°C)
- During winter we recommend to store the rolls on site at room temperature at least 24 hours before use
- Keep the rolls out of direct sunlight
- Rolls must be kept at least 2m from any heat source

Applications



- Void Fill



- Block & Brace

Pregis

The Netherlands
Nijverheidsweg 4,
6422PD Heerlen

United Kingdom
Gunnels Wood Road,
Stevenage, Herts, SG1 2DG

France
9 Bis Avenue Louis de Broglie,
ZI Vert Galant, BP67016
Saint-Ouen l'Aumône, 95050
Cergy Pontoise Cedex

Germany
Nelmannwall 4,
59494 Soest

☎ 00800 8888 8840 | ✉ customer.care@pregis.com

www.pregis.com