

PRO PAK'R

Renew™ Multitube

- Multifunctional
- Air transfer technology
- RFID technology



These AirSpeed Renew air bags are created out of 50% post-consumer recycled content. It is made from products that served end-users, after which it has been recycled. The Renew Multitube film is transparent, because the resins used in these films originate from very clean sources, such as waste from supermarkets. This allows us to create an – almost – transparent air cushion out of post-consumer waste. The information is printed on each air cushion with a water-based ink, so it's not harmful to the environment.

The Multitube is a solution when a variety of applications is required. It allows a high quality protection thanks to the air-transfer technology, which improve shock absorption. Each air cushion is composed of 8 rectangular shaped pouches which offer a higher flexibility of protection.

The film complies perfectly with the European legislation for packaging and packaging waste: EN13427.



Machine & Accessories

The **PRO PAK'R** is equipped with the latest technology. It is fast, smart, easy to use and compact. It works with various films.



Air Cushion Specifications

- Size cushion: WxL = 400x127 mm
- Thickness: 19 micron
- Material: LDPE
- Rather clear and transparent, green print
- 100% recyclable
- Product code: 4093434

Specifications

ROLLS

- Roll length: 665 metre
- Roll weight: 9 kg
- Volume per roll: 6 m³

PALLET

- Rolls per pallet: 54
- Number of layers: 3
- Rolls per layer: 18
- Pallet weight: 540 kg
- Pallet dimensions: LxWxH in cm = 120x80x135



Characteristics

Environmental Friendly

- 100% Recyclable
- Suitable for energy recovery
- Very light, 99% air
- Complies with EN13427 standard for packaging and packaging waste
- Printing is made from water-based ink

Technical Specifications

- Non toxic
- Groundwater neutral
- Chemically inert
- Dust-free
- Wear-resistant
- Can be transported problem free via the existing recycling systems for PE
- Water repellent

Storage Conditions

- Store covered in a clean dry room
- Average storage condition should be 20°C (max. 30°C)
- During winter we recommend to store the rolls on site at room temperature at least 24 hours before use
- Keep the rolls out of direct sunlight
- Rolls must be kept at least 2m from any heat source

Packing Applications



- Block & Brace



- Top layering



- Corner Protection



- Cross-layer



- Wrapping

Pregis