Notorious

Porcelain Stone®

Sizes (Shown in NTRO4)











3 x 15

Mixed Mosaic UPS Finish (Mounted on a 297 x 297 sheet)

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



Sizes & Finishes

Nominal (in) Actual (mm) Thickness (mm) Grout Joint (mm) Finish	
3 x 15 72 x 372 9.5 3 UPS	
12 x 12 297 x 297 9.5 3 UPS/H	NC
12 x 24 297 x 597 9.5 3 UPS/H	NC
24 x 24 597 x 597 9.5 3 UPS/H	NC
24 x 36 597 x 897 10.5 3 UPS/H	NC

All field tile is rectified

Crossville recommends a minimum 3mm grout joint.

4	Mosaics	1	1	Available in all colors	
	Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
	Mixed Mosaic*	297 x 297	9.5	3	UPS

*Mounted on 297 x 297 sheet

Coordinating Trim

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
6 x 12 Cove Base	150 x 297	9.5	3	UPS
4 x 12 Single Bullnose	97 x 297	9.5	3	UPS/HON**

 ** HON finish is special order only.



4 x 12 Single Bullnose (available in all colors)



6 x 12 Cove Base (Universal, flat top)

Product Performance

Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.50 - 0.60	ANSI A326.3
HON	0.42 - 0.52	ANSI A326.3

Shade & Texture Index

Notorious has a shade variation of V2



This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/ shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/ Fountains
UPS	✓	✓	✓	Mosaics Only*		✓	✓
HON	✓	✓	✓			✓	✓

^{* 4&}quot; or less in both length and width, UPS or UP mosaics

NOTE: Trim applications will differ from field tile applications for the same series.

For more information on ANSI- A362.3 visit our website at https://www.crossvilleinc.com/Resources/Tile-101/DCOF?tab=1



^{**} Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information.