

Linen

Come home to Linen by Lunada Bay Tile – a ceramic tile series that envelopes your space in subtle texture and easy style. The handcrafted tiles feature a refined palette of glazes that emanate simple elegance. The tiles pair seamlessly with other collections in the Lunada Bay Tile design house, offering you the opportunity to design surfaces with graceful nonchalance.



SCAN CODE FOR MORE INFORMATION ON THE LINEN COLLECTION

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2024 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior	
Interior Wall/Backsplash	Yes		No	No	
Fireplace/Cooktop Surround	Yes *		No	N/A	
Shower Wall	Yes		Yes	No	
Steam Shower	Yes		No	No	
Exterior Wall	Yes		<i>DCOF Value of ≥ 0.42 is accepted value for use in commercial applications. A 137.1-2018</i>		
Pool, Spa or Water Feature (fully submerged)	Yes				
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF per Piece)	Packaging (Per Box)	Standards Methods		
4" Hex	0.090	44 Pieces/3.939 SF	Breaking Strength	ASTM C-648	> 450 PSI
2 ½ x 9 ½"	0.155	32 Pieces/4.960 SF	Water Absorption	ASTM C-373	Vitreous ≥ 0.5% -≤ 3.0%
4 ¾ x 9 ½"	0.310	16 Pieces/4.960 SF	Chemical Resistance	ASTM C-650	Unaffected
Liner (¾ x 9 ½")	0.787 LF/PC	80 Pieces/63 LF	Freeze/Thaw	ASTM C-1026	Unaffected
Shade Variation	Grout Joint Recommendation		Warpage	ASTM C-485	± 0.26% / ± 1.5mm
V2 Slight Variation	1/8" (3 mm)		NOTES		
			<p>Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).</p>		
			MAINTENANCE		
			<p>A routine cleaning of Linen tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.</p>		

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. **Not** recommended for placement inside a firebox.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.