

PINNACLE

GLAZED PORCELAIN TILES



VINESTREET
— Studios —

PINNACLE

GLAZED PORCELAIN TILES

Pinnacle White



30x60 cm | 12"x24"
AC (SATIN)

Pinnacle Bone



30x60 cm | 12"x24"
AC (SATIN)

Pinnacle Gray



30x60 cm | 12"x24"
AC (SATIN)


Pinnacle Nero



30x60 cm | 12"x24"
AC (SATIN)

Finish
AC (Satin)

Pinnacle White



30x30 cm | 12"x12"
AC (SATIN)
DCOF \geq 0.42

Pinnacle Bone



30x30 cm | 12"x12"
AC (SATIN)
DCOF \geq 0.42

Pinnacle Gray



30x30 cm | 12"x12"
AC (SATIN)
DCOF \geq 0.42

Pinnacle Nero




30x30 cm | 12"x12"
AC (SATIN)
DCOF \geq 0.42

Pinnacle Hex White




20x23 cm | 8"x9"
AC (SATIN)

Pinnacle Hex Bone




20x23 cm | 8"x9"
AC (SATIN)

Pinnacle Hex Gray



20x23 cm | 8"x9"
AC (SATIN)

Pinnacle Hex Nero



20x23 cm | 8"x9"
AC (SATIN)








PINNACLE

GLAZED PORCELAIN TILES

SIZES

		Product	Finish	Rect.	Work Size	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton
	Wall/Floor 12"x 24"	Keystone AC	Satin	No	302.3 x 601.2 mm 11-7/8" x 23-5/8"	7.5 mm	18	17.60	9
	Wall/Floor 12"x 12"	Keystone AC	Satin	No	302.3 x 302.3 mm 11-7/8" x 11-7/8"	7.0 mm	37	16.72	17
	Wall/Floor Hex 8"x 9"	Keystone Hex AC	Satin	No	200.4 x 231.6 mm 7-7/8" x 9-1/8"	8.0 mm	20	9.37	25

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level – Interior Floor (Residential / Light Commercial)	N/A	✓
Wet & Level – Interior Floor (Residential / Light Commercial)	≥ 0.42	✓
Shower Floors (Residential / Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Exterior Walls Applications	N/A	✓
Interior Walls/Backsplashes	N/A	✓
Interior Countertops	N/A	✓
Facades	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

Note: Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 0.5%
Breaking Strength	C648	≥ 275 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	≥0.42
Frost Resistance	C1026	Yes
Surface Abrasion (PEI)	C1027	3 - 4
Scratch Hardness	MOHS	8
Chemical Resistance	C650	Resistant

INSTALLATION AND CARE

Grout Joint Recommendation 1/8" for 12x24 and Hex.; 3/16" for 12x12
Shade Variation V2 - SLIGHT VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

⚠ IMPORTANT DISCLAIMER FOR 12X12 TILES CALIBERS

The 12x12 comes in 4 calibers 9, 0, 1, and 2. The central caliber is 1 and the range within each caliber is 1.4mm. Caliber 9 can work with 0 and caliber 2 can work with 1, but it would not be recommended to install calibers that are not adjacent to each other.

⚠ IMPORTANT DISCLAIMER FOR CHECKERBOARD INSTALLATIONS

If you are planning to create a checkerboard or alternating color pattern using this product, please note the following requirements to ensure a successful installation:

- All calibers and sizes must be inspected prior to installation. Slight variations may occur between different color batches.
- No claims will be accepted after the product has been installed.
- To help us assist you properly, please note your intention to create a checkerboard pattern on your purchase order. This allows our fulfillment team to review and coordinate your order accordingly.

Vine Street Studios' recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Vine Street Studios recommends using a cloth with water and a neutral cleaner (soap less) or a general household cleaner.

QUALITY WARRANTY

QUALITY	Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006, NBR 15463 and NBR 13818, ANSI A137.1 standards.	FIRE PROOF	Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.
VOC FREE	Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).	RECYCLED CONTENT	Recycled content: Pre-consumer Porc. 12x24 : 44.4% Porc. 12x12: TBI Porc. Hex : 31.4% Post-consumer Porc. 12x24 : 0 % Porc. 12x12: TBI Porc. Hex : 8.0 %

Porcelain tiles on this series are:







