


Tozen

Like the art of watercolor, the Tozen collection uses transparency, pigment and light to tell a story. Translucent glass presents our artists the perfect canvas to juxtapose luminosity and darkness...transparency and opacity...rest and movement. The handcrafted, smooth-edged design is available in 19 colors and two finishes to narrate your personal design story.



Up To 70%
Post-Consumer
Recycled Content

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2020 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior	
Interior Wall/Backsplash	Yes		Yes ▲	Yes ▲	
Fireplace/Cooktop Surround	Yes *		Yes ▲	N/A	
Shower Wall	Yes		Yes ▲	No	
Steam Shower	Yes		No	No	
Exterior Wall	Yes		<i>Note: Silk finish is recommended for floor/foot traffic applications and usage.</i>		
Pool, Spa or Water Feature (fully submerged)	Yes **				
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Sheet/Piece)	Packaging (Per Box)	Standards Methods		
½ x ½ Mini Mosaic	1.09	5 Sheets/5.45 SF	Breaking Strength	ASTM C-648	>350 PSI
½ x 1 Mini Brick	1.09	5 Sheets/5.45 SF	Water Absorption	ASTM C-373	Impervious < 0.05%
½ x 4 Brick	0.84	5 Sheets/4.20 SF	Chemical Resistance	ASTM C-650	Unaffected
1 x 1 Mosaic	1.09	5 Sheets/5.45 SF	Freeze/Thaw	ASTM C-1026	Unaffected
1 x 2 Brick	1.00	5 Sheets/5.00 SF	Thermal Shock	ASTM C-484	Passed
1 x 4 Brick	0.85	5 Sheets/4.25 SF	NOTES Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. On dimensional patterns, using a grout bag is the best method to target competent and successful grout application. Grout floats should not be used due to the luster glaze. please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).		
1 x 4 Herringbone	0.69	5 Sheets/3.45 SF			
2 x 6 Brick	5.046	58 Pieces/Box			
Japonaise (½ x 1", 1 x 1")	1.09	5 Sheets/5.45 SF			
Martini (¾ x 2")	1.04	5 Sheets/5.20 SF			
Moyou (½ x 4", 1 x 4")	0.68	5 Sheets/3.40 SF			
Pompeii (½ x ½")	1.08	5 Sheets/5.40 SF			
Rio (½ x 1", 1 x 1")	1.27	5 Sheets/6.35 SF			
Tresse (½ x 1", 1 x 4")	0.78	5 Sheets/3.90 SF			
Wings (1 x 1")	1.03	5 Sheets/5.15 SF			
Shade Variation	Grout Joint Recommendation		MAINTENANCE A routine cleaning of Tozen tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.		
V4 - Random Variation	1/16" (1.6 mm)				

* Acceptable for use near open flame or heat source; However it is **NOT** considered 'Fire Glass'.

** **Size and Pattern Limitations:** 1/2 x 4", 1 x 4", 1 x 4" Herringbone, 2 x 6", Moyou, and Tresse, are **NOT** recommended for use or installation in a submerged application such as a pool/spa or steam shower floors.

▲ **Size and Pattern Limitations:** 2 x 6" is for interior wall and shower wall use only, and is **NOT** recommended for use or installation on floors.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.